

**A global sensitivity methodology to guide risk  
assessment for CO<sub>2</sub> geological storage in deep saline  
aquifers**

Jeremy Rohmer

► **To cite this version:**

Jeremy Rohmer. A global sensitivity methodology to guide risk assessment for CO<sub>2</sub> geological storage in deep saline aquifers. 2nd EAGE workshop on CO<sub>2</sub> geological storage, Mar 2010, Berlin, Germany. hal-00531782


**HAL Id: hal-00531782**

**<https://hal-brgm.archives-ouvertes.fr/hal-00531782>**

Submitted on 3 Nov 2010

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



# Global Sensitivity Methodology to Guide Risk Assessment for CO<sub>2</sub> Geological Storage in Deep Saline Aquifers

Jeremy Rohmer<sup>a</sup>

<sup>a</sup>BRGM, "Natural Hazards and Safety of CO<sub>2</sub> Storage" Division, Orléans, FRANCE

## CONTEXT

European Directive 2009/31/EC on the geological storage of carbon dioxide states: Annex I, Step 3.2: Sensitivity characterisation  
« Multiple simulations shall be undertaken to identify the sensitivity of the assessment to assumptions made about particular parameters. The simulations shall be based on altering parameters in the static geological earth model(s), and changing rate functions and assumptions in the dynamic modelling exercise. Any significant sensitivity shall be taken into account in the risk assessment ».

### Numerical models for risk assessment:

- ⊗ Multiple input parameters
- ⊗ High non-linearities
- ⊗ High computer time cost

Need for appropriate tools to carry out sensitivity analysis based on limited number of model runs

## MODEL

Supercritical CO<sub>2</sub> = 1 Mdy, 10y

P0 = 180 bars, T0 = 75 °C, Depth = 1750 m

200 kms

Input Parameter	Unit	min	MAX
Porosity	%	10	25
Intrinsic permeability	D	0,1	6
Capillary entry pressure P <sub>c</sub>	Pa	20 000	81 000
Van Genuchten Parameter m(VG)	-	0,460	0,600
Residual gas saturation	%	5	25
Residual liquid saturation	%	20	50
Salinity	g/l	5	35
Pore compressibility	Pa <sup>-1</sup>	4.5e-10	9.E-10

➢ 1d multiphase flow transport model;  
➢ Dogger formation (Paris basin case);  
➢ TOUGH2/ECO2n (Pruess, 2005);  
➢ Based on Andre et al., 2007;  
➢ Minimum grid cell of 50 cm;  
➢ Total number of grid cells = 576;  
➢ Number of input parameters=8;  
➢ Number of samples=8x30=240.

Based on: Andre et al., 2007, Bachu and Bennion, 2008, Birkholzer et al., 2009, Rojas et al., 1989

## METHODOLOGY

### Response surface method (Box and Draper, 1987)

$f =$  "real" computing-intensive model  
 $Y =$  output,  $X = [X_1, \dots, X_n]$  = inputs  
 $g =$  meta-model = surrogate "simpler" model to mimic  $f \rightarrow$  "regression model"  
 $Y = f(X) = f(x_1, x_2, \dots, x_n)$   
 $f(X) = g(x_1, x_2, \dots, x_n)$   
Evaluation of  $g$  is faster


### Which meta-model ?

- $g$  can be of several form (Storie and Helton, 2008) :
1. Linear regression  $\Leftrightarrow$  « One at a time »
  2. Quadratic regression
  3. Gaussian Process
  4. Non parametric regression
- When  $f$  highly non linear  
Work fairly well with a modest number of inputs

A method of nonparametric regression:  
**Recursive partitioning regression** (Breiman et al., 1984)  
➢ Split a set  $S$  of observations into  $nP$  subgroups such that the observations within each subgroup  $PS$  are more homogeneous than they are over the whole set  $S$ ;  
➢ The model  $f$  is then estimated by a linear regression over each subgroup  $SG$ ;  
➢  $g =$  piecewise linear function:

$$f(X) = g(X) = \sum_{i=1}^{n+1} (a_i + b_i X) H_i(X)$$

$H_i(X)$  is the Heaviside function,  $(a_i + b_i X)$  is the linear fit to the data associated with  $SG$ .



Extracted from Storie and Helton, 2008 based on the « performance assessment for a radioactive waste disposal facility »

### Step1: Mapping-training data

- Between the input and the output domain  $\{X_i, Y_i\}$  with limited number of samples;
- **Latin hypercube sampling** method (McKay et al., 1979);
- Combined with the "maxi-min" space filling design criterion
- ➔ maximise the exploration of the input domain.

### Step2: Response surface construction

**Objective:** keep only the most important parameters in the surrogate model.  
**Step i.** a 1dim. recursive partitioning regression model is constructed for each candidate parameter  $\rightarrow nX$  1dim response surface models. The parameter, for instance  $x_1$ , associated with the best of these models is identified and selected;  
**Step ii.** 2dim. recursive partitioning regression models are constructed using the best candidate  $x_1$  selected in the first step and each of the remaining  $nX-1$  parameters. The parameter, for instance  $x_2$ , associated with the best of these models is identified and selected;  
**Step iii.**.... Following the same principle, the third parameter is selected and the process is continued until a stopping criterion is reached...  
**Stopping criterion** = p-value (statistical approach of hypothesis testing).

### Step 3: Importance measure

**Coeff. of determination  $R^2 \Leftrightarrow$  Goodness of fit**  
$$R^2 = \frac{\sum_{i=1}^n (g(X^i) - Y_i)^2}{\sum_{i=1}^n (f(X^i) - \bar{Y})^2}$$
  
**The order** the input parameter enters the response surface = importance order;  
At each step of the response surface construction  $R^2 =$  importance measure of the input parameter;  
Additional validation through **cross-validation** (use observations from the initial training data as the validation data, and the remaining samples as the new training data for a new response surface construction, e.g. Hjorth, 1994).

## SENSITIVITY RESULTS

### RISK in the injection zone

- 1 Leakage through wells
- 2 Local fracturing

### RISK at large scale

- 3 Large scale over-pressurization
- 4 Expected lateral plume extent exceeded

Adapted from Bouc et al., 2009

#### Extent of the drying-out zone

#### Maximum pressure

#### Extent of the over-pressurized zone at 50 % of Pmax

#### Extent of the CO2 plume

#### Total free gas

#### Extent of the over-pressurized zone (cutoff=0.1 bar)

➢ Goodness of fit  $R^2 > 99.0$  for all models;  
➢ Coeff. of determination of the **cross-validation**  $Rcv^2 > 98.0$  for all models;  
➢ The effect of **salinity** appears to be negligible;  
➢ The **pore compressibility** should be taken into account for the large scale pressure impact;  
➢ **Residual gas and liquid saturation** have an important effect considering trapping and has a moderate effect for CO<sub>2</sub> plume extent and over-pressurized zone (at 50 % of Pmax);  
➢ Capillary entry pressure only affects the extent of the drying-out zone near the injector;  
➢ Small effect of the **Van-Genuchten's parameter m**;  
➢ Both **porosity & intrinsic permeability**  $\approx 80$  % of the effect on all considered risk outputs.

## References

André, L., Audigane, P., Azaroual, M., Menjor, A., 2007. Numerical modeling of fluid-rock chemical interactions at the supercritical CO<sub>2</sub>-liquid interface during CO<sub>2</sub> injection into a carbonate reservoir, the Dogger aquifer (Paris Basin, France). Energy Conversion and Management, 48, 1782-1797.  
Bachu, S., Bennion, B., 2008. Effects of in-situ conditions on relative permeability characteristics of CO<sub>2</sub>-brine systems. Env. Geology, 54(8), 1707-1722.  
Birkholzer, J.T., Zhou, Q., Tsang, C.-F., 2009. Large-scale impact of CO<sub>2</sub> storage in deep saline aquifers: a sensitivity study on the pressure response in stratified systems. International Journal of Greenhouse Gas Control 3,181-194.  
Bouc, O., Audigane, P., Bellenfant, G., Fabriol, H., Gastine, M., Rohmer, J., Seyedi, D., 2009. Determining safety criteria for CO<sub>2</sub> geological storage. Energy Procedia, 1(1), 2439-2446.  
Box, G.E., Draper, N.R., 1987. Empirical model building and response surfaces. Wiley series in probability and mathematical statistics, Wiley, New York.  
Breiman, L., Friedman, J.H., Olshen, R.A., Stone, C.J., 1984. Classification and regression trees, Chapman Hall, New York.  
European Commission, 2009. Directive 2009/31/EC of the European Parliament and of the Council of 23 April 2009 on the geological storage of CO<sub>2</sub>  
Hjorth, J.S.U., 1994. Computer Intensive Statistical Methods: Validation Model Selection and Bootstrap, Chapman and Hall, London, UK.  
McKay, M.D., Beckman, R.J., Conover, W.J., 1979. A comparison of three methods for selecting values of input variables in the analysis of output from a computer code. Technometrics, 21, 239-245.  
Pruess, K., 2005. ECO2N: A TOUGH2 Fluid Property Module for Mixtures of Water, NaCl, and CO<sub>2</sub>. Report LBNL-57952. LBNL, Berkeley, CA, USA.  
Rojas, J., Giot, D., Le Nindre, Y.M., Craud, A., Fouillac, C., Brach, M., 1989. Caractérisation et modélisation du réservoir géothermique du Dogger, bassin parisien, France. Technical Report CCE, EN 3G-0046-F(CD). BRGM R 30 IRG SGN 89.  
Storie, C.B., Helton, J.C., 2008. Multiple predictor smoothing methods for sensitivity analysis: Description of techniques, Rel. Eng. & Syst. Saf., 93, 28-54.

**Acknowledgments**  
This work was funded under the BRGM's Research project "Gestion des Risques" integrated in the Directorate of Research project CSRCR3.

J. ROHMER  
j.rohmer@brgm.fr  
BRGM