1
2
3
4
5
6 **Experiments and Numerical Modelling of Microbially-Catalysed**
7 **Denitrification Reactions**
8
9

10
11
12 By L. André*, H. Pauwels, M.-C. Dictor, M. Parmentier, M. Azaroual,

13
14 BRGM, 3 Avenue C. Guillemin, BP 36009, F-45060 Orléans Cedex 2, France
15

16
17 *** Corresponding author:**

18 Laurent ANDRE

19 l.andre@brgm.fr

20 Tel : +33 238 64 31 68

21 Fax : +33 238 64 37 19
22
23
24

25 Submitted to Chemical Geology
26
27

28 First submission December 2010

29 Revised manuscript April 2011
30
31
32

Abstract

Denitrification processes have been studied for many decades in both the laboratory and the field, and current work investigates heterotrophic and autotrophic denitrification reactions. Physical, chemical and microbiological parameters have been shown to control these degradation processes and the fate of nitrogen. In this paper, we describe results and modelling of denitrification reactions in batch and flow-through column experiments. The processes controlling the fate of nitrate and, more specifically, its reduction mediated by micro-organisms are explained in detail by a multi-step process. Modelling involves a rate law describing microbial respiration. Batch experiment data and the results of thermo-kinetic modelling of biogeochemical processes are in relatively good agreement, indicating that the coupled numerical approach is suitable for simulating each individual mechanism involved in denitrification phenomena. The calculated mass-balance indicates that about 40 % of the carbon from acetate is used for anabolism and 60 % for catabolism. The kinetic parameters estimated from the batch experiments are also suitable for reactive transport modelling of laboratory flow-through column experiments. In these experiments performed on pyrite-bearing schist, 80 % of the nitrate reduction is attributed to heterotrophic micro-organisms and 20 % to autotrophic bacteria. These results also indicate that for denitrification in the presence of acetate, the thermodynamic factor in the coupled thermodynamic/kinetic law can be disregarded and denitrification kinetics will be governed, for the most part, by electron donor/acceptor concentrations. This consistency between the results of closed and open systems is a prerequisite for the field-scale use of this type of numerical approach and the efficient and safe management of nitrogen sources. Breaking down the process into several steps makes it possible to focus on the main parameters that enhance the denitrification rate.

Keywords: denitrification; thermodynamic driving force; kinetics; micro-organisms

1. Introduction

Groundwater nitrate (NO_3^-) concentrations exceed human health criteria in many places as a result of anthropogenic inputs such as industrial emissions and synthetic fertilizers and manure used in agriculture (Squillace et al., 2002; McCallum et al., 2008; and references therein). Nitrate is now very commonly found in groundwater in Europe and North America (Matějů et al, 1992; Rivett et al, 2008). This creates environmental problems and has even led to the halting of pumping in many well fields. Techniques to decrease nitrate concentrations include ion exchange, reverse osmosis and biological denitrification (Matějů et al, 1992).

Denitrification (or dissimilatory nitrate reduction) is recognised as being an efficient natural microbially-mediated nitrogen removal process in soils and waters (Dahab, 1987; Rivett et al., 2008; Aelion and Warttinger, 2010). Indeed, groundwater nitrate can be attenuated by denitrification processes that reduce NO_3^- according to a series of reactions mediated by micro-organisms under anaerobic conditions (Knowles, 1982; Tavares et al., 2006; Rivett et al., 2008):

This has been widely observed in natural environments such as wetlands (Bowden, 1987; Whitmire and Hamilton, 2005; Scott et al., 2008), hyporheic zones (Duff and Triska, 1990; Jones et al., 1995; Sheibley et al., 2003) and shallow and deep aquifers (Lovley and Chapelle, 1995; Pauwels et al., 1998, 2010; Pinay and Burt, 2001; Molénat et al., 2002; Ruiz et al., 2002). Denitrification, with either heterotrophic (Her and Huang, 1995; Aslan, 2005) or autotrophic bacteria (Koenig and Liu, 2001; Park and Yoo, 2009), is also used to treat drinking water.

All of these nitrate bioremediation processes use denitrifying bacteria, which, like other micro-organisms in soil, water, sediments and oceans, play a major role in the biogeochemical cycles of major and trace elements (carbon, nitrogen, sulphur, phosphorus, iron, mercury, selenium, arsenic, etc.) (Dommergues and Mangenot, 1970; Stevenson and Cole, 1999; Madigan et al., 2000; Ehrlich, 2002). Most of these bacteria are able to use the energy of redox reactions to proliferate under aerobic or anaerobic conditions (Decker et al., 1970; Mitchell, 1961). They act as a catalyst for reactions in which electrons are transferred from a donor to an acceptor species. This microbial activity also links electron transfer to proton transfer through the cell membrane, enabling the synthesis of adenosine triphosphate (ATP) from adenosine diphosphate (ADP) and intracellular phosphate ions (P_i). However, this reaction occurs only if the energy of the corresponding redox reaction is high enough to provide the energy for bacterial metabolism as an excess enthalpy (Jin and Bethke, 2002). Bacterial behaviour in natural aqueous systems is therefore closely linked to redox reactions (Lindberg and Runnels, 1984; Keating and Bahr, 1998; Michard, 2002).

These observations highlight the connexions between chemical and biological processes and the need to take into account a coupled thermodynamic/kinetic approach in order to accurately predict the global behaviour of such systems. Many theoretical and empirical approaches have

100 been developed to describe biogeochemical processes. These include the enzyme reaction
101 kinetic model proposed by Michaelis and Menten (1913) and the bacterial growth kinetics
102 model proposed by Monod (1949). The latter is used most often to describe the relationship
103 between bacterial growth and substrate concentration (Rittmann and McCarty, 2001). This
104 approach, while very successful for batch systems, has significant limitations. It is suitable for
105 irreversible reactions and conditions far from thermodynamic equilibrium where chemical
106 energy is not a limiting factor (Curtis, 2003; Jin and Bethke, 2007; Torres et al., 2010). It
107 cannot, however, correctly predict reaction rates when substrate concentrations drop below a
108 substrate threshold value (Lovley, 1985, Cord-Ruwisch et al., 1988; Giraldo-Gomez et al.,
109 1992). Like other empirical rate laws, it does not consider that, close to thermodynamic
110 equilibrium, there is not enough available energy to meet the needs of micro-organisms for
111 microbial metabolism, maintenance and other cellular functions (Jin and Bethke, 2007).

112
113 Because of the large number and the complexity of the elementary mechanisms involved, the
114 numerical modelling of these processes requires the use of powerful and relevant theoretical
115 approaches in the calculation codes. To enable us to progress in our understanding of the
116 biogeochemical behaviour of ecosystems, robust numerical tools must consider not only
117 chemical and thermodynamic processes (i.e. Gibbs free enthalpy of the redox reactions), but
118 also biological phenomena (i.e. bacterial growth). Among the various patterns proposed to
119 simulate these coupled processes, that of Jin and Bethke (2003, 2005, 2007) appears to be the
120 most comprehensive because it considers both the chemical characteristics of the system
121 (through electron donor/acceptor concentrations) and thermodynamic conditions (through the
122 Gibbs free enthalpy of the redox reactions involved), which are the driving forces of the
123 biogeochemical processes. The suitability of this approach (thereafter called "the Jin and
124 Bethke approach") and the role of the thermodynamic potential factor have been
125 demonstrated for degradation processes with the thermodynamic control of the respiration
126 rate during arsenate reduction (Jin and Bethke, 2003), methanogenesis or sulfate reduction
127 (Jin and Bethke, 2005). In these examples, the respiration process is expected to cease, even if
128 significant amounts of both electron donors and acceptors are still available for
129 metabolization. The role of thermodynamics has also been described concerning the progress
130 of enzymatic reactions like benzoate, crotonate and glucose fermentations (Jin and Bethke,
131 2007).

Because denitrification is a complex process mediated by micro-organisms, this coupled thermokinetic/biogeochemical approach would seem to be highly suitable for simulating the biogeochemical reactions occurring between nitrate and electron donors in water. Such a model could be useful for the management of natural environments, particularly to estimate denitrification rates in groundwater for long-term groundwater protection or for the implementation of corrective measures to decrease the impact of diffuse sources. We describe here a versatile model that does not oversimplify the biogeochemical system (overall reaction of nitrate to N_2) and is suitable for denitrification catalyzed by different microbial consortia. This model includes a multi-step denitrification process that enables better control of the numerous thermokinetic parameters involved by considering all reaction products. This model tests the suitability of the Jin and Bethke approach for each individual mechanism (the “driving forces” of each process). It defines the limiting and weight parameters and we use it to investigate how natural consortia influence the dynamics of denitrification. The model also enables integration of different microbial communities having specific influence on denitrification process. This model allows for evaluation of the relationship between anabolism and catabolism for the heterotrophic micro-organisms under consideration and it enables estimation of the fraction of denitrification that is caused by autotrophic and/or heterotrophic bacteria.

This work is based on laboratory denitrification experiments (batch and packed bed column done with inoculum from groundwater that contains both heterotrophic and autotrophic bacteria), and yields numerical simulations of the biogeochemical reactions involved in the denitrification processes. Its objectives were to (i) identify the main steps that control the kinetic rate of the denitrification process, (ii) highlight an approach using both batch and flow-through column experiments, (iii) characterize the role played by micro-organisms during each reaction, and (iv) develop a comprehensive biogeochemical model of denitrification.

2. Experiments and Modelling

2.1 Experimental approach

2.1.1 Choice of experimental conditions

Denitrification experiments conducted in this study were done with water and rock samples collected in the Coët-Dan catchment, 70 km SW of Rennes (Brittany), in western France, where low nitrate concentrations in groundwater have been attributed to advanced denitrification mechanisms (Pauwels et al., 2001, 2010). The presence of pyrite in the aquifer rock contributes to a high-rate denitrification reaction (Pauwels et al., 1998) mediated by autotrophic bacteria according to the simplified reaction:

Heterotrophic denitrification involving organic matter has, however, also been reported (Pauwels et al., 2001, 2004).

Groundwater was collected with a submersible pump and stored in a sterile vessel after three well volumes of water had been purged. The well enabled the collection of water at a depth between 7 and 15 m – a redox zone where there is denitrification (Pauwels et al., 2001). Aliquots were filtered through 0.45 µm pore size for chemical analysis. Aliquots for cation measurements were acidified to pH 2. Alkalinity was measured by titration with HCl. Major cation (Na^+ , K^+ , Ca^{2+} and Mg^{2+}) and anion (NO_3^- , NO_2^- , Cl^- and SO_4^{2-}) concentrations were measured by HPLC, and total iron by spectrophotometry. Dissolved organic C was measured by pyrolysis at 680 °C with CO_2 infrared detection (TOC 5000 Shimadzu).

The bacterial analysis done on a raw groundwater sample with the “Most Probable Number” method (Halvorson and Ziegler, 1933) confirmed the presence of (i) heterotrophic denitrifying bacteria, (ii) *Thiobacillus denitrificans* (about 2,500 cells mL^{-1}) and (iii) *Acidithiobacillus ferrooxidans* (fewer than 0.5 cells mL^{-1}). Most of the population is able to reduce nitrate to nitrite (about 5,870 cells mL^{-1}), whereas only a small fraction is able to reduce nitrate to N_2 (about 130 cells mL^{-1}).

Only heterotrophic denitrification was considered for batch experiments, whereas by using schist, both heterotrophic and autotrophic processes were involved during the flow-through column experiment. Experiments were done in the presence of acetate (model organic compound). This enabled us to break down the global mechanism and quantify the kinetics of the various denitrification steps (Eqs. 2 to 4).

2.1.2 Batch experiments

Batch assays were done in glass serum flasks (500 mL) supplemented with 150 mL (biotic flasks) or 300 mL (abiotic flasks) of sampled groundwater (Table 1). The headspace was flushed with CO₂ gas to remove oxygen from the flasks. CO₂ was chosen instead of N₂ or CO₂ + N₂ mixtures in order to avoid a secondary nitrogen source in a nitrogen-enriched medium. The flasks were sterilised by autoclaving at 120 °C for 20 minutes. The biotic flasks were inoculated with 150 mL of non-sterile groundwater. Six flasks were prepared – 3 biotic flasks and 3 abiotic flasks. Ten millilitres (10 mL) of a 3,000-mg KNO₃ L⁻¹ solution were added to the medium to give a final concentration of 50 mg NO₃⁻ L⁻¹ and 50 mL of a 1476.4-mg Na₂CH₃COO L⁻¹ solution were added to give a final concentration of 50 mg acetate L⁻¹. A trace-element solution (0.25 mL) containing the following, in mg L⁻¹, was added to this: EDTA, 500; MnSO₄, H₂O, 2.6; FeSO₄, 200; ZnSO₄, 7 H₂O, 10; H₃BO₃, 30; CoCl₂, 6 H₂O, 20; CuCl₂, 2 H₂O, 1; NiSO₄, 7 H₂O, 2.4; and Na₂MoO₄, 2 H₂O, 3.

Water and gas samples were collected at regular intervals to monitor the reaction.

2.1.3 Flow-through column experiment

Denitrification was studied in a glass column (0.45 L) equipped with an external water jacket that maintained the temperature at 14 °C throughout the experiment (Fig. 1). The column had an internal diameter of 3.5 cm and was 32 cm high. It was packed with 599.3 g of crushed schist (200 µm, see Table 2 for mineralogical assemblage) and sterilised 3 times at 24-hour intervals by autoclaving for 1 hour at 121 °C.

After sterilisation, the column was inoculated with a denitrifying bacteria consortium specially prepared for this experiment. The enrichment culture, prepared with a groundwater sample, was made up in sterile 500 mL serum flasks containing a culture medium composed of 150 mg L⁻¹ of KNO₃, 5.66 mg L⁻¹ of Na-acetate and 1 mL of the trace-element solution described above. The pH of the medium was adjusted to 6.5 with a 1 molar H₂SO₄ solution. The serum flasks were then flushed with N₂ gas to ensure anaerobic conditions. The enrichment culture was incubated for 3 weeks at 14 ± 2 °C. Aliquots were sampled periodically to monitor bacterial growth and the nitrate concentration in the flask.

The experiment was done with synthetic water prepared with chemicals reagents (Table 3). The nitrate-bearing solution was injected into the column after the inoculum solution for 200 hours in two phases:

- Phase 1 (between 0 and 100 hours). The column was fed continuously with synthetic solution 1 (Table 3) in the up-flow mode by an adjustable peristaltic pump (flow rate = 0.25 mL min⁻¹). The major element concentrations in the injected aqueous solution were similar to those of the groundwater (Table 1). Before it was injected into the column (Fig. 1), the synthetic medium was continuously sparged with CO₂ gas and placed in a thermostatic chamber (14°C).
- Phase 2 (between 100 and 200 hours). A carbon source (acetate) with a concentration of 10 mg C L⁻¹ (Table 3) was added to the synthetic solution 2.

An automatic sampler (Gilson) was connected to the outlet column in order to periodically collect water samples.

The hydrodynamic characteristics of the column were determined by injecting a conservative tracer, NaBr, before the denitrification experiment began. A pulse of the tracer at a constant flow rate (0.25 mL min⁻¹) was injected and the outlet concentration of bromide was monitored with time. Based on the bromide breakthrough curve, the mean residence time was estimated to be 12.5 hours. The dispersivity coefficient, 0.02 m, was determined by modelling the flow transport with PHREEQC (Parkhurst and Appelo, 1999). A pore volume of 190 cm³, corresponding to a mean porosity of 35 %, was calculated from the residence time and the injection flow rate.

2.1.4 Analytical procedure

Nitrate, nitrite and acetate concentrations were determined during the batch and flow-through column experiments by ion chromatography with a DIONEX IC3000-SP-EG-DC system equipped with an AS50 autosampler and a conductimetric detector. A gradient elution with sodium hydroxide, from 10 to 100 mM, was applied at 1 mL min⁻¹ at 30 °C through an anionic column (DIONEX-AG19 and AS19 HC, 4 mm ID). An aliquot was sampled for bacteria counting using a Thoma cell by optic microscopy (Zeiss 400x). N₂O in gas samples was analysed with a chromatograph (VARIAN 3800) equipped with a gas injection valve and an electron capture detector.

For the flow-through column experiment, the samples were collected in glass tubes previously flushed with nitrogen and sealed. The tubes were opened in an anaerobic glove box for analyses. One aliquot of raw sample was used for bacteria counting. pH and oxido-reduction potential (ORP) were measured on the raw sample and the remaining water was filtered at 0.45 µm for anionic analyses (NO₃⁻, NO₂⁻, SO₄²⁻, Cl⁻, CH₃COO⁻) by ion chromatography.

2.2 Numerical modelling approach

Micro-organisms affect the geochemical cycle of many chemical species by catalysing chemical reactions while the physicochemical properties of the environment control the activities of micro-organisms by providing habitats, nutrients, and energy (Jin and Bethke, 2007). Physicochemical, thermodynamic/kinetic and biological phenomena must, therefore, be accurately predicted before we can determine the fate of chemical species (reactants and products), microbial population activity and microbial growth. Modelling requires a robust numerical model able to account for all of these strongly linked characteristics and the evolving properties.

2.2.1 Thermodynamic and biological coupling

Various kinetic rate laws and coupled models have been proposed to describe the thermokinetics of bacterial growth (Hoh and Cord-Ruwisch, 1996; Fennel and Gossett, 1998; Hunter et al., 1998; Noguera et al., 1998; Kleerebezem and Stams, 2000; Knab et al., 2008). They are all based on Monod's equation and often add terms containing a thermodynamic factor (such as the reaction quotient Q/K, where Q is the ionic activity product and K is the equilibrium

constant of the reaction) or a minimum free energy ($\Delta G_{\min}$). However, most of these approaches were developed to describe specific physiological systems with constant $\Delta G_{\min}$ values. The approach proposed by Jin and Bethke (2002, 2003, 2005, 2007) goes further and seems to be more suitable and flexible because it associates (i) a kinetic factor for an electron donor, (ii) a kinetic factor for an electron acceptor, (iii) a term for bacterial growth, and (iv) a thermodynamic factor. Furthermore, the Jin and Bethke approach makes it possible to propose a consistent reactive transport model for hydro-geochemical systems with kinetically dissolving/precipitating minerals for which the reaction quotient Q/K is used in the context of the Transition State Theory (Lasaga, 1984; Palandri and Kharaka, 2004).

The Jin and Bethke approach is based on the relationship between chemical redox reactions and microbial growth under natural conditions. Redox reactions, which are often slow, can, in some rare cases, be at thermodynamic equilibrium or close to it (Lindberg and Runnels, 1984; Keating and Bahr, 1998; Michard, 2002; Stefansson et al., 2005). In natural systems, the progress of redox reactions is usually catalysed by micro-organisms. During this process, bacteria use some of the released energy to synthesize adenosine triphosphate (ATP) from adenosine diphosphate (ADP) and the orthophosphate ion (intracellular PO_4^{3-} , denoted P_i) (Eq. 5):

where v_D , v_A , v_{D^+} and v_{A^-} are the stoichiometric coefficients of chemical species (D = donor, A = acceptor). The ATP serves as a chemical energy reserve (stock).

From this, Jin and Bethke (2002) derived a comprehensive kinetic law (Eq. 6) that can account quantitatively for the thermodynamic driving force of redox reactions:

$$v = k[X] F_D F_A F_T \quad (6)$$

where v is the overall rate of microbial respiration ($\text{mol L}^{-1} \text{s}^{-1}$), k is the intrinsic kinetic constant ($\text{mol g}^{-1} \text{s}^{-1}$) and $[X]$ is the biomass concentration (g L^{-1}). F_D and F_A (ranging from 0 to 1, dimensionless) are kinetic factors accounting for the effects of the concentration of dissolved chemical species involved in redox reactions (Eqs. 7 and 8):

$$F_D = \frac{\prod_D [D]^{\beta_D}}{\prod_D [D]^{\beta_D} + K_D \prod_{D^+} [D^+]^{\beta_{D^+}}} \quad (7)$$

$$F_A = \frac{\prod_A [A]^{\beta_A}}{\prod_A [A]^{\beta_A} + K_A \prod_{A^-} [A^-]^{\beta_{A^-}}} \quad (8)$$

where β_D , β_A , β_{D^+} , β_{A^-} are exponents of reactant and product concentrations. Their values are not predicted by theory and depend on details of the electron transport mechanism (Jin and Bethke, 2003). K_D and K_A are constants for electron donor D and acceptor A.

F_T (ranging from 0 to 1, dimensionless) is the thermodynamic potential of the overall reaction corresponding to the driving force of the reaction (Eq. 9):

$$F_T = 1 - \exp\left(\frac{\Delta G_{\text{redox}} + m \Delta G_P}{\chi RT}\right) \quad (9)$$

where ΔG_{redox} is the free enthalpy of the reaction, ΔG_P is the phosphorylation energy, and χ is the average stoichiometric coefficient of the overall reaction. The coefficient m is the number of synthesised ATP defined in the overall reaction (Eq. 5).

2.2.2 Numerical modelling approach

The Jin and Bethke approach was included in the geochemical code PHREEQC (Parkhurst and Appelo, 1999) to deal with denitrification in the presence of acetate. This approach requires, however, that the database used by the calculation code be modified. In its standard use, this code is based on chemical equilibrium calculations of aqueous solutions interacting with minerals and gases using general and extended thermodynamic databases, and aqueous redox reactions are considered to be at equilibrium. As this is rarely the case (Stefansson et al., 2005), a kinetic term must be introduced for redox reactions. PHREEQC is a very flexible code for simulating chemical reactions in the aqueous phase and enables the re-writing of aqueous redox reactions to account for kinetic constraints. Since this study focuses on nitrate behaviour, all redox reactions involving nitrogen were re-written to take into account the kinetics of successive transformations (decreasing redox number: $N(V) \rightarrow N(III) \rightarrow N(II) \rightarrow N(I) \rightarrow N(0)$). The chemical equilibria between nitrate-nitrite- N_2O and N_2 were removed from the

database and replaced by kinetic laws. Only aqueous complexing reactions of nitrate and nitrite with cations and vapour-liquid equilibrium for N_2O and N_2 were kept.

2.2.3 Thermo-kinetic simulation of denitrification processes

The coupled thermodynamic-biogeochemical approach is applied to the reduction of (i) nitrate to nitrite (Eq. 2), (ii) nitrite to nitrous oxide (Eq. 3) and (iii) nitrous oxide to nitrogen (Eq. 4). These reactions are kinetically constrained, whereas thermodynamic equilibria are retained between all other species in the aqueous phase including nitrogen species (ligand) complexing cations. The term F_T in Eq. (9) was determined based on the following assumptions. The phosphorylation enthalpy (ΔG_P) is roughly estimated to be 50 kJ mol^{-1} under typical physiological conditions (White, 1995), whereas χ and m are reaction-dependent parameters. For Eq. (2), $\chi = 2$ and $m = 2/3$. Two protons are transferred by electron pairs and three are required for ATP synthesis (Jin and Bethke, 2005). For Eqs. (3) and (4), few data are available in the literature. Consequently, the same values for χ and m were used for the three reactions (Eqs. 2 to 4) (Q. Jin, personal communication, August 2009). Gibbs free enthalpies of each reaction (ΔG_{redox}), determined at each time step from the free standard enthalpy of each reaction are $-140.12 \text{ kJ mol}^{-1}$, $-248.92 \text{ kJ mol}^{-1}$ and $-314.43 \text{ kJ mol}^{-1}$ for Eqs. (2) to (4), respectively (Michard, 2002).

In Eqs (7) and (8), the functions $K_D \cdot \prod [D^+]^{\beta_{D^+}}$ and $K_A \cdot \prod [A^-]^{\beta_{A^-}}$ are kinetic terms that replace the half-saturation constant in the Monod equation. In a first approximation, the kinetic term can be expected to be equivalent to the half-saturation constant only when the thermodynamic potential is close to 1 (Jin and Bethke, 2005) or when, under appropriate geochemical conditions such as when the pH is buffered, there is a large substrate concentration and no build-up of metabolic products (Jin and Bethke, 2007). In this study, as demonstrated below, the pH is buffered and the thermodynamic factor is close to 1 throughout the reaction. Consequently, the two kinetic terms are replaced by two half-saturation constants (K'_D and K'_A). For step 1 of denitrification (Eq. 2), the values used are from Clément et al. (1997): $K'_D = 1.20 \text{ mg L}^{-1}$ and $K'_A = 0.66 \text{ mg L}^{-1}$. As no data are available for nitrite (Step 2 – Eq. 3) or N_2O (Step 3 – Eq. 4), we used the same values for K'_A and K'_D as those determined for nitrate.

375

376 A growth yield of 0.13 mg-biomass/mg-NO₃⁻ (Clément et al., 1997) was used for step 1 (Eq.
 377 2). For steps 2 and 3 (Eqs. 3 and 4), Clément et al. (1997) did not give a value for growth
 378 yields. Values found in the literature indicate that the growth yield for nitrite is about three
 379 times that for nitrate (Peyton et al., 2001): a value of 0.40 mg-biomass/mg-NO₂⁻ was therefore
 380 used. For nitrous oxide, as no literature data were found, the same value as the one for nitrate
 381 was chosen arbitrarily (0.09 mg-biomass/mg-N₂O). For calculations, a conversion factor of
 382 6.2 10⁹ cells mg⁻¹ biomass was used to convert experimental data (in cells mL⁻¹) to input data
 383 for numerical model (in mg-biomass mL⁻¹) (Clément et al., 1997).

384

385 Because denitrification by heterotrophic bacteria is studied, the model must also take into
 386 account the microbial growth using carbon from acetate and nitrogen from each nitrogen-
 387 bearing species in solution. For the numerical simulations, the biomass is represented using a
 388 simplified generic form (C₅H₇O₂N) and integrated into Eqs. (2) to (4). The growth yield
 389 determined above provides information concerning the stoichiometry of the reaction, i.e. the
 390 number of moles of biomass synthesised from nitrate, nitrite and nitrous oxide consumption.
 391 Consequently, Eqs. (2) to (4) are rewritten:

392

393

394

395

396 These stoichiometric equations, which take into account the biomass growth (anabolism),
 397 were incorporated in the geochemical code. Although bacterial death obviously also affects
 398 the micro-organism population during the experiments, it was disregarded. We assumed that
 399 no significant nutrients (or chemical components) coming from dead bacteria are released into
 400 solution.

401

402

3. RESULTS AND DISCUSSION

3.1 Batch experiments

3.1.1 *N-species*

Batch experiments focused on measuring kinetic parameters for the entire denitrification reaction, from nitrate to N₂. The abiotic flasks used as blanks show no denitrification during the entire experimental time. We know, therefore, that the nitrate attenuation observed in the biotic flasks is due to biological rather than chemical processes.

The results obtained on biotic flasks indicate a total denitrification in 40 days. Each experiment began with a period of about eight days during which the nitrate concentration did not vary (Fig. 2). Under our experimental conditions, micro-organisms seem to need time to adjust before denitrification begins. Nitrate reduction starts after 8 days with a decrease in nitrate correlated with the formation of nitrite in solution.

This first nitrate reduction reaction lasts about 30 days. At this time, nitrogen (+V) has been completely reduced to nitrogen (+III) and nitrite is the major aqueous nitrogen species. Only small and transitory amounts of N₂O are found in solution. Significant quantities of this species appear in solution when nitrite begins to be reduced by micro-organisms. The N₂O concentration then increases steadily before N₂ appears and nitrogen(I) is finally reduced to nitrogen(0).

Modelling is based on experimental constraints and the results obtained, using the Jin and Bethke approach, are described above. The kinetic constants for each reaction are:

- Nitrate to nitrite: An initial period (day 0 to day 8) during which no measurable microbial activity and no denitrification is recorded, is followed by a second period (day 8 to day 29) during which nitrate is reduced to nitrite consistent with a mean kinetic constant of $4.6 \cdot 10^{-7} \text{ mol N L}^{-1} \text{ h}^{-1}$.
- Nitrite to nitrous oxide: A first period (day 0 to day 29), up to complete nitrate reduction, during which the nitrite reduction rate is assumed to be nil, is followed by a second period (day 30 to day 40) during which the nitrite reduction rate is about $2.3 \cdot 10^{-7} \text{ mol N L}^{-1} \text{ h}^{-1}$.

- Nitrous oxide to nitrogen: The kinetic rate is highly dependent on nitrate and nitrite concentrations. Up to the total reduction of nitrate (day 0 to day 29), the nitrous oxide reduction rate is assumed to be nil, whereas thereafter (day 29 to day 60), a value of $2.1 \cdot 10^{-7} \text{ mol N L}^{-1} \text{ h}^{-1}$ provides a rather good fit of the observed results.

By coupling batch experiments and numerical modelling we were able to define the different steps of the denitrification process and determine the respective kinetic rates. The kinetic rate for the first reduction step (nitrate to nitrite) falls within the range reported in the literature (from $5.0 \cdot 10^{-7}$ to $2.0 \cdot 10^{-6} \text{ mol-N L}^{-1} \text{ h}^{-1}$) for denitrification with organic matter (Star and Guillham, 1993; Schipper and Vojvodic Vukovic, 1998, 2000; Devlin et al., 2000). This experiment shows that the reduction of nitrite (and the formation of nitrous oxide) is related to nitrate consumption. As long as nitrate is present, nitrite increases and is measurable in solution. In natural environments, high nitrite concentrations are rarely observed, except in specific cases (Kelso et al., 1999). In laboratory systems, this nitrite accumulation is often observed by the use of acetate as the electron donor. Carbon sources such as acetate and propionate cause nitrite to accumulate in the medium, which does not occur with butyrate, valerate or coproate (Wilderer et al., 1987; van Rijn and Tal, 1996). These authors assume that in the presence of acetate, nitrite accumulation is caused by differences in nitrate and nitrite reduction rates and by the competition between nitrate and nitrite reduction pathways for electrons. Our experiments confirm this hypothesis of competition between the two reduction processes in the presence of acetate – nitrite reduction does not start until all of the nitrate has been consumed, favouring nitrate reduction before nitrite reduction and the nitrite accumulation.

3.1.2 pH pattern

The pH is initially stable or decreases slightly (during nitrate reduction to nitrite, up to day 29), and then increases during nitrite reduction (day 29 to day 40, Fig. 3). Calculated pH values fit the experimental data relatively well and the major trends are reproduced, except for some small discrepancies in the first part of the experiment. During nitrate reduction (Eq. 2), a small increase in pH is predicted by numerical calculations due to proton consumption, whereas experimental data show a slight decrease. The slopes of the curves for observed and simulated results are identical for the nitrite reduction reaction. Eq. (3) indicates that the proton consumption is higher than in the previous nitrate reduction reaction – the consequence of this being a change in the slope with a relatively greater increase in pH

between day 30 and day 40. However, pH does not vary greatly due to the buffering capacity of the reactive aqueous solution.

3.1.3 Acetate as the electron donor

Acetate is the electron donor used by micro-organisms to promote the heterotrophic denitrification reaction. The concentration is constant during the first 8 days (when no nitrate is consumed) and then decreases sharply (Fig. 4). After 40 days, there is no longer any acetate (for 2 of the 3 replicates). The simulation correctly fits the observed data, except for one of the replicates, for which no explication can be found, since all of the other measured variables (nitrogen species concentration, pH, biomass concentration) are consistent for the three replicates. Numerical simulations confirm that all of the acetate is consumed during the experiment. It is used to synthesize CO₂ (catabolism) and biomass (anabolism) (Eqs. 10 to 12). When numerical modelling was done without taking the bacteria anabolism into consideration (Fig. 4 - dashed line) only about 30 mg of acetate are used to reduce 50 mg of nitrate (Eqs. 2 to 4).

Acetate is the source of both the electrons and the carbon needed by bacteria to proliferate. This is highlighted by the two simulations. One considers only catabolism, while the other takes into account both the anabolism and the catabolism of the micro-organisms (Fig. 4). Results using the first scenario do not match the measured acetate concentrations, whereas those using the second scenario agree with the observed acetate consumption data. This second scenario indicates that about 40 % of the carbon from acetate is used for anabolism and 60 % is used for catabolism. From Eqs. (10) to (12), the calculated mass-balance confirms that 41 % of the carbon coming from acetate is used for biomass production, in agreement with literature data. For aerobic degraders, Greskowiak et al. (2005) proposed a value of 60 % for anabolism, meaning that 40 % of the carbon is converted to CO₂. However, for anaerobic denitrification in the presence of acetate, this ratio is reversed. Clément et al. (1997) defined a biomass growth yield of about 20 %, whereas Odencrantz et al. (1990) and Istok et al. (2010) have proposed values of 37.5 % and 41 %, respectively.

3.1.4 Biomass growth

Fig. 5 shows the evolution of the biomass in the batch experiment. The bacterial population increases rapidly (day 0 to day 8) before decreasing and then increasing once again. It stabilizes after 40 days (i.e. the end of nitrite reduction). The bacterial growth model, based on nitrate, nitrite and nitrous oxide reduction, produces results that are in relatively good

agreement with experimental data. The overall trend and the final biomass concentration are in agreement with observed data. The only discrepancy concerns the first period (day 0 to day 8). Some bacterial activity, independent of the denitrification process since nitrate reduction and acetate oxidation are nil (or extremely low) during this period, is assumed to influence the biomass population and probably pH during this period. The batch experiments were done with groundwater initially containing both heterotrophic and autotrophic bacteria. Autotrophic bacteria (very active in the field) might develop during the experiment in the aqueous solution. These use the mineral carbon (bicarbonate), and their activity might explain the biomass peak and the slight decrease in pH (Fig. 3). This is hypothetical, however, and since it does not play a major role in the overall denitrification process, it was disregarded in the numerical calculations.

The measurements of biomass concentration in the three replicates also show that the bacterial growth stabilizes after 40 days, in correlation with the total consumption of electron donors and acceptors. Acetate and nitrate – rather than the bioavailability of other elements – seem to be the limiting factors of bacterial activity. As an example, a simple calculation of the amount of phosphorus needed shows that, assuming a classical formulation $\Delta C:\Delta N:\Delta P \approx 106:16:1$ for dry biomass (Sigg et al. 2000), a few $\mu\text{mol P L}^{-1}$ are necessary to generate the concentrations of biomass measured in the three replicates. The calculated P concentration and the limit of quantification have the same order of magnitude. We therefore assume that the natural groundwater used for these experiments provides enough trace elements (such as phosphorus) for the growth of the bacterial community.

3.1.5 Remarks on the Thermodynamic Potential Factor

One objective of this study was to determine the relative weight of kinetic factors influencing global denitrification. The thermodynamic potential factor (F_T) remains constant (and equal to 1) throughout the experiment (Figs. 6 and 7). For denitrification in the presence of acetate, the thermodynamic factor has no affect on denitrification. For step 1 (i.e. reduction from nitrate to nitrite – Eq. 2), the denitrification process is governed by the kinetic factor (F_A) related to the electron acceptor concentration (i.e. nitrate), whereas for step 2 (i.e. reduction from nitrite to nitrous oxide – Eq. 3), the kinetics of denitrification is limited by F_A (i.e. nitrite concentration) and mainly F_D factors (i.e. acetate concentration). For denitrification in the presence of acetate (Figs. 6 and 7), the thermodynamic factor can be disregarded and the global kinetics of denitrification are governed mainly by the concentrations of electron donors/acceptors. The

model proposed by Jin and Bethke is, however, entirely suitable for simulating bacteria-mediated changes in the redox state of a complex biogeochemical system.

3.2 Flow-through column experiment

Flow-through column experiments should help us better understand the influence of flow on water chemistry, in particular on the denitrification process. Tarits et al. (2006) have demonstrated the influence of hydrodynamic factors on water chemistry. They point out that denitrification is activated by pumping in the aquifer. In columns and, more generally, in consolidated porous media, microbial communities can also develop in biofilms, creating locally variable redox conditions and processes (Yu and Bishop, 1998; Bishop and Yu, 1999). Our column experiment provides an opportunity to observe whether the denitrification kinetic rates determined using batch experiments are always valid and can be used as is in transport experiments. The breakthrough curves for nitrate and nitrite are given in Fig. 8 and for chloride and sulphate in Fig. 9.

The nitrate concentration increases until it reaches a constant value equal to the input concentration (50 mg L^{-1}). The nitrite concentration is lower than 2 mg L^{-1} (Fig. 8). The synthetic solution 1 (Table 3) has lower chloride and sulphate concentrations than the inoculum solution initially introduced in the column. This explains the decrease in the outlet concentrations of these two ions during the first hours of the experiment (Fig. 9). Between 50 and 100 hours, the outlet concentrations for chloride, sulphate and nitrate are the same as the inlet concentrations: the system reaches a steady state. No denitrification occurs in the column during this period despite the presence of bacterial inoculum in the system and of pyrite in the schist (Table 2).

At time = 100 hours, phase 2 of the experiment begins with the input of a carbon source. A solution containing nitrate (50 mg L^{-1}), acetate (10 mg L^{-1}) and sulphate (33.78 mg L^{-1}) is injected into the column (synthetic solution 2, Table 3). The nitrate concentration at the outlet of the column decreases immediately and the nitrite concentration increases. About 50 % of the injected nitrate has been reduced to nitrite and to reduced nitrogen species after 190 hours (Fig. 8). Nitrate removal is not in a steady state. It is more rapid between 100 and 130 hours than during the period between 130 and 200 hours. Nitrite concentrations followed the opposite trend with a sharp increase between 100 and 130 hours and a smoother variation thereafter (130 to 200 hours). The chloride concentration does not vary when the injected

solution changes, whereas the sulphate concentration does. Since synthetic solution 2 contains less sulphate than synthetic solution 1, a decrease in the sulphate concentration was expected. Although a small drop was observed, the outlet concentration of this species was always greater than the injected concentration, as opposed to what occurred during the previous phase (0 to 100 hours). Sulphates are therefore produced within the column, and we conclude that dissolved sulphates come from an interaction between the aqueous solution and minerals. Considering the mineralogical assemblage of the constituting rock (pyrite-bearing schist), the sulphur production is attributed to the dissolution/oxidation reaction of pyrite. During this stage (100 to 200 hours), two electron donors impact on the denitrification process – acetate (Eqs. 2 to 4) and pyrite (Eq. 1).

Based on the results of the column experiment, we assume that the bacterial inoculum used to colonize the schist was composed mainly of heterotrophic bacterial species. The specific medium, enriched in acetate and used to develop this inoculum, probably favours the growth of heterotrophic bacteria (Tranvik and Höfle, 1987), which have a specific growth rate higher than that of autotrophic micro-organisms (Tsai and Wu, 2005). Marchand and Silverstein (2002) also show that heterotrophic microbial growth could have an impact on the behaviour of autotrophic populations, in particular on the biological oxidation of pyrite. They suggest that the development of heterotrophic micro-organisms might inhibit the rate and the extent of sulphide mineral oxidation. This experiment highlights the major role played by heterotrophic bacteria in the denitrification process since it is initiated by the addition of organic matter to the injected solution.

The absence of denitrification due to the oxidation of pyrite by nitrate during the first period (0 to 100 hours) was not expected since microbial denitrification had been observed at the site where the samples were collected (Pauwels et al., 1998). However, these authors did not specify whether the autotrophic micro-organisms were chemolithotrophic bacteria (which use inorganic carbon as a carbon source and non-carbon compounds as an electron source, Chapelle 2001) or chemoorganotrophic bacteria (which use inorganic carbon as a carbon source and carbon compounds as an electron source, Chapelle 2001). From field measurements, they simply identified the preponderant role of autotrophic bacteria compared to that of heterotrophic bacteria. The results of our experiment show that chemoorganotrophic bacteria had been fostered by the acetate-enriched medium used to develop the inoculum, whereas chemolithotrophic bacteria, probably present in the inoculum but in low numbers, were not active enough to initiate the denitrification process. Consequently, the low

population of chemolithotrophic micro-organisms and the absence of organic matter for chemoorganotrophic bacteria prevented any decrease in the nitrate concentration during this first period.

The column experiment was modelled with PHREEQC using a 1D column (discretised into 10 sections, each 3 cm long) with hydrodynamic characteristics determined using the bromide tracer (see paragraph 2.1.2). The simulation complies with the two-phase experiment: injection of a nitrous solution without organic carbon (synthetic solution 1, Table 3) during the first 100 hours, followed by injection of a nitrate/acetate solution (synthetic solution 2, Table 3) from hour 100 to hour 200. A constant injection flow rate is imposed at the inlet of the column and a Cauchy boundary condition is assumed at the outlet. A biomass concentration of $1.6 \cdot 10^7$ cells mL^{-1} is assumed at the beginning at the experiment.

For the biogeochemical part of the simulation, the kinetic parameters determined in batch systems with acetate were used without modification (Eqs. 10 to 12). However, in this flow-through column experiment, the kinetic rate for reaction 1 (i.e. pyrite oxidation, Eq. 1) had to be estimated ($3.2 \cdot 10^{-7}$ mol N L^{-1} h^{-1}) based on field data (Postma et al., 1991; Pauwels et al., 1998). To our knowledge, there is no literature data for the parameters used to calculate the thermodynamic factor of reaction 1 (Eq. 1). Only the free enthalpy can be calculated: -456 kJ mol^{-1} (Michard, 2002). This value is high (of the same order of magnitude as that of acetate), and in batch experiments it was demonstrated that the thermodynamic factor is close to 1 with such a high ΔG_0 . In a first approximation, for this calculation, the thermodynamic factor is assumed to be 1. A Monod approach is then used for reaction 1 (Eq. 1). This is justified due to the high free enthalpy of the reaction and the excess of pyrite in the schist (Pauwels et al., 1998).

The kinetic rates used for each reaction make it possible to reproduce the experimental values for nitrate, nitrite (Fig. 8) and sulphate (Fig. 9). The outlet sulphate concentrations, calculated from the inlet SO_4 concentration and the number of moles of pyrite oxidized by nitrates (Reaction 1, Eq. 1), are in good agreement with the observed data (Fig. 9). A small difference between measured and calculated sulphate concentrations is observed at 120 hours. Numerical modelling predicted a small peak in sulphate that is not observed. In the column experiment, the autotrophic bacteria have a short time lag, which is not considered in the numerical approach since the two bacterial processes (heterotrophic and autotrophic) are activated at the

same time. This simultaneous activation might explain the punctual over-estimation of the sulphate concentration.

The numerical simulation of the second part of the experiment (between 100 and 200 hours) also confirms that the bacteria active in the column are, for the most part, heterotrophic since the outlet nitrate concentration starts to decrease when acetate is co-injected with nitrate. However, heterotrophic denitrification alone cannot explain the measured decrease in the nitrate concentration. Autotrophic denitrification must also be involved to match the observed data. The two autotrophic processes (chemoorganotrophic and chemolithotrophic) are also assumed to be active in this experiment. Indeed, the addition in the injected solution of a carbon source (acetate) can activate the chemoorganotrophic mechanism. Moreover, heterotrophic bacteria produce alkalinity (mainly as dissolved CO_2), due to acetate degradation for their catabolism. According to the reactions described in Eqs. (10) to (12), 1 mole of nitrate induces the formation of about 1.8 moles of $\text{CO}_{2,\text{aq}}$. This increase in alkalinity could explain the increased activity of chemolithotrophic bacteria. All of these processes are assumed to be active in the column experiment.

The absence of any source of organic matter, therefore, prevents the development of chemoorganotrophic activity. The low alkalinity of the injected solution also stops the activity of chemolithotrophic bacteria. With the addition of acetate, the heterotrophic bacteria are activated and produce alkalinity, which is immediately used by chemolithotrophic micro-organisms. We also assume that chemoorganotrophic bacteria are activated by the carbon availability. However, neither the data nor the model can explain the relative weight of each autotrophic community. This simultaneous heterotrophic/autotrophic denitrification has been described for nitrate removal from high-nitrate wastewater (Gommers et al., 1988; Aminzadeh et al., 2010). These authors emphasize the high efficiency of such a treatment, which enables the removal of sulphide, acetate and nitrate in natural and synthetic wastewater in fluidized bed reactors. Oh et al. (2002) calculated that the reduction of 1 mg of nitrate nitrogen, with methanol, generates 3.57 mg of CaCO_3 . According to these authors, the two processes are linked and a lack of any organic source can decrease the performance of denitrification treatment.

Modelling of both heterotrophic and autotrophic processes correctly reproduces the observed outlet concentrations of nitrate, nitrite and sulphate. The outlet nitrate concentration after 200

hours is close to 30 mg L⁻¹ (for an inlet concentration of 50 mg L⁻¹), which means that the two species of bacteria are able to remove about 40 % of the initial nitrate. A comparison of two calculations (results not shown here), one done with and the other without considering the autotrophic mechanism, indicates that 80 % of the nitrate consumption is due to heterotrophic denitrification and the remainder is due to autotrophic processes. The numerical results for the nitrite concentration are in good agreement with the observed data. As the modelling approach considers only the production of nitrite by the heterotrophic process, we deduce that autotrophic denitrification does not release any nitrite into solution (or that the kinetic rate of nitrite production equals the kinetic rate of nitrite consumption). This absence of nitrite accumulation (via pyrite oxidation) has been observed in NO₃⁻-reducing cultures (Van Beer, 2000; Weber et al., 2001).

The experimental results of this flow-through column experiment show no time lag when acetate is injected into the column. In batch experiments, there is no heterotrophic microbial activity during the first 8 days (Fig. 2). In the field, Pauwels et al. (1998) observed an autotrophic metabolic lag of about 40 hours. The absence of a microbial adjustment period can be attributed to the experimental protocol:

- During the first phase of the experiment (the first 100 hours), the microbial population was accustomed to a NO₃⁻-containing solution, thus limiting the beginning of microbial activity, when acetate was added.

- The flow rate through the column is low compared to the flow rate in field studies where transport processes have a greater impact on denitrification (Pauwels et al., 1998). Moreover, the column experiment is done using crushed schist. Consequently, the exchanges, the contact surface and, therefore, the interactions between aqueous solution, mineral (in particular pyrite) and micro-organisms are probably more favourable, decreasing the time lag.

4. CONCLUSIONS

This study focuses on heterotrophic and autotrophic denitrification processes, i.e. the reduction of nitrate (NO₃⁻) to nitrogen (N₂). Although denitrification in soils and aquifers is studied extensively for water quality, diffuse pollution transfer, and remediation, there is still an on-going debate in the scientific community concerning the contribution of organic matter

as an electron donor when other mineral electron donors (i.e. pyrite) are available. The main goals of this study were therefore:

- to better understand denitrification processes in complex systems (water-rock-organic matter-microorganisms) using experiments and numerical modelling of elementary processes and,
- to conceptualize numerical modelling based on a decoupled thermodynamic database that enables the integration of the new thermo-kinetic approach of Jin and Bethke (2002), clearly splitting available energy in terms of three driving forces, i.e. catabolism, anabolism and a surviving reserve.

This new, comprehensive thermokinetic rate law based on energetic approaches takes into consideration both the thermodynamic driving force and biogeochemical processes. This approach is applied successfully to the heterotrophic denitrification processes in the presence of acetate coupled with the autotrophic contribution based on pyrite oxidation.

The thermodynamic and kinetic parameters incorporated in the geochemical code PHREEQC reproduce the concentrations of nitrate-bearing species during the entire duration of the batch experiment. This computer code is robust enough to model the behaviour of chemical species (electron donor, electron acceptor, pH, etc.), biological aspects (anabolism and catabolism of the biomass population) and energy conditions (thermodynamic factor linked to the reaction energy). The comparison of model and observed results confirms that each step of nitrate reduction in the presence of acetate is governed mainly by kinetic factors and not limited by thermodynamic constraints. The energies of the reactions (in the presence of an electron donor like acetate) are too high compared to the energy needed by micro-organisms to proliferate. Consequently, this factor is not limiting and nitrate reduction is complete if there is an excess of electron donors.

Nevertheless, although this thermodynamic approach is not useful for denitrification with acetate, it cannot be applied to all denitrification processes in the presence of other electron donors. The main factor influencing the thermodynamic factor is the free enthalpy of the reactions – the reactions with acetate and pyrite are very energetic (several hundreds of kJ mol⁻¹) whereas the free standard enthalpy of reactions with goethite or amorphous iron hydroxides are low (several tens of kJ mol⁻¹). This approach should, therefore, be of value for dealing with denitrification involving goethite or amorphous oxides as electron donors.

This work, which uses both batch and column experiments, shows that these two approaches are complementary. The kinetic data set determined at the batch scale (similar to literature data) is sufficiently well constrained to simulate nitrate, nitrite and biomass concentrations. The numerical simulations indicate that during the heterotrophic denitrification reaction, about 40 % of the carbon from acetate is used for anabolism, whereas 60 % is used for catabolism. Moreover, this set of parameters, fitted with results from batch experiments, can be successfully used to model the column experiment, a 1D system. The heterotrophic denitrification in the column and batch experiments can be explained by the same process, which is promising for application to field studies. Numerical modelling is therefore a useful tool for managing natural environments when the numerous thermo-kinetic parameters are known.

ACKNOWLEDGEMENT

We thank C. Crouzet and S. Touzelet (BRGM/Metrology, Monitoring and Analysis Division) for their assistance with experiments and chemical analyses, and S. Kremer (BRGM/Water Division) for her help modifying geochemical databases. The authors also thank two anonymous reviewers for helpful comments and suggestions.

REFERENCES

- Aelion, C.M., Wartinger, U., 2010. Low sulfide concentrations affect nitrate transformations in freshwater and saline coastal retention pond sediments. *Soil Biol. Biochem.*, 41(4), 735-741.
- Aminzadeh, B., Torabian, A., Azimi, A.A., Nabi Bidhendi, Gh.R., Mehrdadi, N., 2010. Salt inhibition effects on simultaneous heterotrophic/autotrophic denitrification of high nitrate wastewater. *Int. J. Environ. Res.*, 4(2), 255-262.
- Aslan, S., 2005. Combined removal of pesticides and nitrates in drinking waters using biodenitrification and sand filter system. *Process Biochem.*, 40, 417-424.
- Bishop, P.L., Yu, T., 1999. A microelectrode study of redox potential change in biofilms. *Water Sci. Technol.*, 39(7), 179-185.
- Bowden, W.B., 1987. The biogeochemistry of nitrogen in freshwater wetlands. *Biogeochemistry*, 4, 313-348.

755 Chapelle, F.H., 2001. Ground-Water Microbiology and Geochemistry, 2nd ed. New York:
756 John Wiley and Sons.

757 Clément, T.P., Peyton, B.M., Skeen, R.S., Jennings, D.A., Petersen J.N., 1997. Microbial
758 growth and transport in porous media under denitrification conditions: experiments
759 and simulations. *J. Cont. Hydrol.*, 24, 269-285.

760 Cord-Ruwisch, R., Seitz, H., Conrad, R., 1988. The capacity of hydrogenotrophic anaerobic
761 bacteria to compete for traces of hydrogen depends on the redox potential of the
762 terminal electron acceptor. *Arch. Microbiol.*, 149, 350-357.

763 Curtis, G.P., 2003. Comparison of approaches for simulating reactive solute transport
764 involving organic degradation reactions by multiple terminal electron acceptors.
765 *Computers and Geosciences*, 29, 319–329.

766 Dahab, M.F., 1987. Treatment alternatives for nitrate contaminated groundwater supplies. *J.*
767 *Environ. Syst.* 17, 65-75.

768 Decker, K., Jungermann, K., Thauer, R.K., 1970. Energy production in anerobic organism.
769 *Angew. Chem. Int. Ed. Engl.* 9, 138-158.

770 Devlin, J.F., Eedy, R., Butler, B.J., 2000. The effects of electron donor and granular iron on
771 nitrate transformation rates in sediments from a municipal water supply aquifer. *J.*
772 *Cont. Hydrol.*, 46, 81-97.

773 Dommergues, Y., Mangenot, F., 1970. *Ecologie microbienne du sol*. Masson Ed., Paris, 783
774 pp.

775 Duff, J.H., Triska, F.J., 1990. Denitrification in sediments from the hyporheic zone adjacent
776 to a small forested stream. *Can. J. Fish. Aquat. Sci.*, 47, 1140-1147.

777 Ehrlich, H.L., 2002. *Geomicrobiology*. 4th edition. New York: Marcel Dekker, 768 pp.

778 Fennell, D.E., Gossett, J.M., 1998. Modeling the production of and competition for hydrogen
779 in a dechlorinating culture. *Environ. Sci. Technol.*, 32, 2450-2460.

780 Giraldo-Gomez, E., Goodwin, S., Switzenbaum, M. 1992. Influence of mass transfer
781 limitations on determination of the half saturation constant for hydrogen uptake in a
782 mixed-culture CH₄-producing enrichment. *Biotechnol. Bioeng.*, 40, 768-769.

783 Gommers, P.J.F., Buleveld W., Zijderwijk, F.J.M., Kuenen, J.G., 1988. Simultaneous sulfide
784 and acetate oxidation in a denitrifying fluidized bed reactor—II. Measurements of
785 activities and conversion. *Wat. Res.*, 22(9), 1085-1092.

786 Greskowiak, J., Prommer, H., Vanderzalm, J., Pavelic, P., Dillon, P., 2005. Modeling of
787 carbon cycling and biogeochemical changes during injection and recovery of
788 reclaimed water at Bolivar, South Australia. *Water Resour. Res.*, 41, W10418.

789 Halvorson, H.O., Ziegler, N.R., 1933. Applications of statistics to problems in bacteriology. I.
 790 A means of determining bacterial population by the dilution method. *J. Bacteriol.*, 25,
 791 101-121.

792 Her, J.J., Huang, J.S., 1995. Influence of carbon source and C/N ratio on nitrate/nitrite
 793 denitrification and carbon breakthrough. *Bioresour. Technol.*, 54, 45–51.

794 Hoh, C.Y., Cord-Ruwisch, R., 1996. A practical kinetic model that considers end product
 795 inhibition in anaerobic digestion processes by including the equilibrium constant.
 796 *Biotechnol. Bioengin.* 51, 597-604.

797 Hunter, K.S., Wang, Y., Van Cappellen, P., 1998. Kinetic modeling of microbially-driven
 798 redox chemistry of subsurface environments: coupling transport, microbial
 799 metabolism and geochemistry. *J. Hydrol.*, 209, 53-80.

800 Istok, J.D., Park, M., Michalsen, M., Spain, A.M., Krumholz, L.R., Liu, C., McKinley, J.,
 801 Long, P., Roden, E., Peacock, A.D., Baldwin, B., 2010. A thermodynamically-based
 802 model for predicting microbial growth and community composition coupled to system
 803 geochemistry: Application to uranium bioreduction. *J. Cont. Hydrol.*, 112, 1-14.

804 Jin, Q., Bethke, C.M., 2002. Kinetics of electron transfer through the respiratory chain.
 805 *Biophys. J.* 83, 1797-1808.

806 Jin, Q., Bethke, C.M., 2003. A new rate law describing microbial respiration. *Appl. Env.*
 807 *Microb.* 69, 2340-2348.

808 Jin, Q., Bethke, C.M., 2005. Predicting the rate of microbial respiration in geochemical
 809 environments. *Geochim. Cosmochim. Acta* 69, 1133-1143.

810 Jin, Q., Bethke, C.M., 2007. The thermodynamics and kinetics of microbial metabolism. *Am.*
 811 *J. Sc.*, 307, 643-677.

812 Jones, J.B., Fisher, S.G., Grimm, N.B., 1995. Nitrification in the hyporheic zone of a desert
 813 stream ecosystem. *J. N. Am. Benthol. Soc.*, 14(2), 249–258.

814 Keating, E.H., Bahr, J.M., 1998. Reactive transport modeling of redox geochemistry:
 815 Approaches to chemical disequilibrium and reaction rate estimation at a site in
 816 northern Wisconsin. *Water Resour. Res.*, 34, 3573-3584.

817 Kelso, B.H.L., Smith, R.V., Laughlin, R.J., 1999. Effects of carbon substrates on nitrite
 818 accumulation in freshwater sediments. *Appl. Environ. Microbiol.*, 65(1), 61-66.

819 Kleerebezem, R., Stams, A.J.M., 2000. Kinetics of syntrophic cultures: a theoretical treatise
 820 on butyrate fermentation. *Biotechnol. Bioengin.*, 67, 528-543.

821 Knab, N.J., Dale, A.W., Lettmann, K., Fossing, H., Jørgensen, B.B., 2008. Thermodynamic
822 and kinetic control on anaerobic oxidation of methane in marine sediments. *Geochim.*
823 *Cosmochim. Acta*, 72, 3746-3757.

824 Knowles, R., 1982. Denitrification. *Microb. Rev.* 46, 43-70.

825 Koenig, A., Liu L.H., 2001. Kinetic model of autotrophic denitrification in sulphur packed-
826 bed reactors. *Water Res.*, 35, 1969–1978.

827 Lindberg, R.D., Runnels, M.D., 1984. Ground water redox reactions: an analysis of
828 equilibrium state applied to Eh measurements and geochemical modelling. *Science*
829 225, 925-927.

830 Lasaga, A.C., 1984. Chemical kinetics of water-rock interactions. *J. Geophys. Res.*, 89, 4009–
831 4025.

832 Lovley, D.R. 1985. Minimum threshold for hydrogen metabolism in methanogenic bacteria.
833 *Appl. Environ. Microbiol.*, 49, 1530-1531.

834 Lovley, D.R., Chapelle, F.H., 1995. Deep subsurface microbial processes. *Rev. Geophys.*, 3,
835 365–381

836 McCallum, J.E., Ryan, M.C., Mayer, B., Rodvang, S.J., 2008. Mixing-induced groundwater
837 denitrification beneath a manured field in southern Alberta, Canada. *Appl. Geochem.*,
838 23(8), 2146-2155.

839 Madigan, M.T., Martinko J.M., Parker, J., 2000. *Brock Biology of Microorganisms*. 9th
840 edition. Prentice Hall, Upper Saddle River, NJ.

841 Marchand, E.A., Silverstein, J., 2002. Influence of heterotrophic microbial growth on
842 biological oxidation of pyrite. *Environ. Sci. Technol.*, 36, 5483-5490.

843 Matějů, V., Čížinská, S., Krejčí, J., Janoch, T., 1992. Biological water denitrification - A
844 review. *Enzyme Microb. Technol.*, 14, 170-183.

845 Michaelis, L., Menten, M.L., 1913. Die Kinetik der Invertinwirkung. *Biochemische*
846 *Zeitschrift*, 49, 333–369.

847 Michard, G., 2002. *Chimie des eaux naturelles. Principe de Géochimie des Eaux*. Editions
848 PUBLISUD, 461 p.

849 Mitchell, P., 1961. Coupling of phosphorylation to electron and hydrogen transfer by a
850 chemiosmotic type of mechanism. *Nature*, 191, 144-148.

851 Molénat, J., Durand, P., Gascuel-Oudou, C., Davy, P., Gruau, G., 2002. Mechanisms of
852 nitrate transfer from soil to stream in an agricultural watershed of French Brittany.
853 *Wat. Air Soil Pollut.*, 133, 161–183.

854 Monod, J., 1949. The growth of bacterial cultures. *Ann. Rev. Microbiol.* 3, 371-393.

855 Noguera, D.R., Brusseau, G.A., Rittmann, B.E., Stahl, D.A., 1998. Unified model describing
856 the role of hydrogen in the growth of *Desulfovibrio Vulgaris* under different
857 environmental conditions. Biotechnol. Bioengin. 59, 732-746.

858 Odencrantz, J.E., Bae, W., Valocchi, A.J., Rittmann, B.E., 1990. Stimulation of biologically
859 active zones (BAZ's) in porous media by electron-acceptor injection. J. Cont. Hydrol.,
860 6, 37-52.

861 Oh, S.E., Bum, M.S., Yoo, Y.B., Zubair, A., Kim, I.S., 2002. Nitrate removal by simultaneous
862 sulfur utilizing autotrophic and heterotrophic denitrification under different organics
863 and alkalinity conditions: batch experiments. Wat. Sci. Technol., 47(1), 237-244.

864 Palandri, J.L., Kharaka, Y.K., 2004. A compilation of rate parameters of water-mineral
865 interaction kinetics for application to geochemical modeling: U.S. Geological Survey
866 Water-Resources Investigations Report 04-1068.

867 Park, J.Y., Yoo, Y.J., 2009. Biological nitrate removal in industrial wastewater treatment:
868 which electron donor we can choose. Appl. Microbiol. Biotechnol., 82, 415–429.

869 Parkhurst, D.L., Appelo C.A.J., 1999. User's guide to PHREEQC (version 2): A computer
870 program for speciation, batch-reaction, one-dimensional transport, and inverse
871 geochemical calculations. U.S. Geological Survey Water-Resources Investigations
872 Report 99-4259, 312 p.

873 Pauwels, H., Kloppmann, W., Foucher, J-C., Martelat, A., Fritsche, V., 1998. Field tracer test
874 for denitrification in a pyrite-bearing schist aquifer. Appl. Geochem. 13(6), 767-778.

875 Pauwels, H., Lachassagne, P., Bordenave, P., Foucher, J.-C., Martelat, A., 2001. Temporal
876 variability of nitrate concentration in a schist aquifer and transfer to surface waters.
877 Appl. Geochem. 16(6), 583-596.

878 Pauwels, H., Talbo, H., 2004 - Nitrates concentration in wetlands: assessing the contribution
879 of different water bodies from anion concentrations. Water Research, 38, 1019-1025.

880 Pauwels, H., Ayraud, V., Aquilina, L., Molénat, J., 2010. The fate of nitrogen and sulfur in
881 hard-rock aquifers as shown by sulfate-isotope tracing. Appl. Geochem. 25(1), 105-
882 115.

883 Peyton, B.M., Mormile, M.R., Petersen, J.N., 2001. Nitrate reduction with *Halomonas*
884 *Campisalis*: kinetics of denitrification at pH 9 and 12.5% NaCl. Water Res., 35, 4237-
885 4242.

886 Pinay, G., Burt, T.P., 2001. Nitrogen Control by Landscape Structures. Research Project
887 1997-2000, EC DGXII. Environment and Climate: ENV4-CT97-0395, February 2001.
888 Final Report 1997–2000.

889 Postma, D., Boesen, C., Kristiansen, H., Larsen F., 1991. Nitrate reduction in an unconfined
890 sandy aquifer: water chemistry, reduction processes and geochemical modeling. *Water*
891 *Resour. Res.* 27, 2027-2045.

892 Rittmann, B.E., McCarty, P.L., 2001. *Environmental Biotechnology: Principles and*
893 *Applications*. McGraw-Hill Companies, Inc., New York (USA), 754 pp.

894 Rivett, M.O., Buss, S.R., Morgan, P., Smith, J.W.N., Bemment, C.D., 2008. Nitrate
895 attenuation in groundwater: A review of biogeochemical controlling processes. *Water*
896 *Res.*, 42, 4215-4232.

897 Ruiz, L., Abiven, S., Durand, P., Martin, C., Vertes, F., Beaujouan, V., 2002. Effect on nitrate
898 concentration in stream water of agricultural practices in small catchments in Brittany:
899 I. Annual nitrogen budgets. *Hydrol. Earth Syst. Sci.* 6, 507–513.

900 Schipper, L., Vojvodic Vukovic, M., 1998. Nitrate Removal from Groundwater using a
901 Denitrification Wall Amended with Sawdust: Field Trial. *J. Environ. Qual.* 27, 664-
902 668.

903 Schipper, L., Vojvodic Vukovic, M., 2000. Nitrate Removal from Groundwater and
904 Denitrification Rates in a Porous Treatment wall Amended with Sawdust. *Ecol. Eng.*
905 14, 269-278.

906 Scott J.T., McCarthy, M.J., Gardner, W.S., Doyle, R.D., 2008. Denitrification, dissimilatory
907 nitrate reduction to ammonium, and nitrogen fixation along a nitrate concentration
908 gradient in a created freshwater wetland. *Biogeochemistry*, 87, 99–111.

909 Sheibley, R.W., Jackman, A.P., Duff, J.H., Triska, F.J., 2003. Numerical modeling of coupled
910 nitrification–denitrification in sediment perfusion cores from the hyporheic zone of the
911 Shingobee River, MN. *Adv. Water Resour.*, 26(9), 977-987.

912 Sigg, L., Behra, P., Stumm, W., 2000. *Chimie des milieux aquatiques; chimie des eaux naturelles et des*
913 *interfaces dans l'environnement*, 3rd ed. Paris: Dunod.

914 Squillace, P.J., Scott, J.C., Moran, M.J., Nolan, B.T., Kolpin, D.W., 2002. VOCs, pesticides,
915 nitrate, and their mixtures in ground-water used for drinking water in the United
916 States. *Environ. Sci. Technol.*, 36, 1923–1930.

917 Starr, R.C., Gillham R.W., 1993. Denitrification and organic carbon availability in two
918 aquifers. *Ground Water*, 31, 934-947.

919 Stefansson, A., Arnorsson, S. and Sveinbjörnsdóttir, A.E., 2005. Redox reactions and
920 potentials in natural waters at disequilibrium. *Chem. Geol.*, 221, 289-311.

921 Stevenson, F.J., Cole, M.A., 1999. *Cycles of soil: carbon, nitrogen, phosphorus, sulfur,*
922 *micronutrients*. 2nd Edition, John Wiley and Sons, 427 pages.

- Tarits, C., Aquilina, L., Ayraud, V., Pauwels, H., Davy, P., Touchard, F. and Bour, O., 2006. Oxido-reduction sequence related to flux variations of groundwater from a fractured basement aquifer (Ploemeur area, France). *Appl. Geochem.*, 21(1), 29-47.
- Tavares, P, Pereira, A.S., Moura, J.J.G., Moura, I., 2006. Metalloenzymes of the denitrification pathway. *J. Inorganic Biochem.*, 100, 2087-2100.
- Torres, C.I., Marcus, A.K., Lee, H.-S., Parameswaran, P., Krajmalnik-Brown, R., Rittmann, B.E., 2010. A kinetic perspective on extracellular electron transfer by anode-respiring bacteria. *FEMS Microbiol. Rev.*, 34, 3–17.
- Tranvik, L.J., Höfle, M.G., 1987. Bacterial Growth in Mixed Cultures on Dissolved Organic Carbon from Humic and Clear Waters. *Appl. Environ. Microbiol.*, 53(3): 482-488.
- Tsai, Y.P., Wu, W.M., 2005. Estimating biomass of heterotrophic and autotrophic bacteria by our batch tests. *Environ. Technol.*, 26(6), 601-614.
- Van Beer, C.G.E.M., 2000. Redox processes active in denitrification. Chapter 12 in: *Redox: fundamentals, processes and applications*. Springer-Verlag Berlin Heidelberg New-York, Inc, 110 Figures, 21 Tables.
- Van Rijn, J., Tal, Y., 1996. Influence of volatile fatty acids on nitrite accumulation by a *Pseudomonas stutzeri* strain isolated from a denitrifying fluidized bed reactor. *Appl. Environ. Microbiol.*, 62(7), 2615-2620.
- Weber, K.A., Picardal, F.W., Roden, E.E., 2001. Microbially catalysed nitrate-dependent oxidation of biogenic solid-phase Fe(II) compounds. *Environ. Sci. Technol.*, 35, 1644-1650.
- Wilderer, P.A., Jones, W.L., Dau, U., 1987. Competition in denitrification systems affecting reduction rate and accumulation of nitrite. *Water Res.*, 21(2), 239-245.
- White, D., 1995. *The physiology and biochemistry of prokaryotes*. Oxford University Press, New York, N.Y.
- Whitmire, S.L., Hamilton, S.K., 2005. Rapid removal of nitrate and sulfate in freshwater wetland sediments. *J. Environ. Qual.*, 34, 2062–2071.
- Yu, T., Bishop, P.L., 1998. Stratification of microbial metabolic processes and redox potential change in an aerobic biofilm studied using microelectrodes. *Water Sci. Technol.*, 37(4), 195–198.

Figure Captions

- Fig. 1. Schematic representation of the flow-through column
- Fig. 2. Evolution with time of the concentration of N-bearing species. Symbols correspond to experimental data with error bars. Lines represent modelling results
- Fig. 3. Evolution with time of pH. Points and dashed lines correspond to measured data of the three replicates. The solid line represents calculated pH values
- Fig. 4. Evolution with time of acetate concentration. Points with dotted lines correspond to measured data of the three replicates. The bold lines represent calculated values: dashed bold line = calculation without considering the bacterial anabolism; solid bold line = calculation with anabolism and catabolism
- Fig. 5. Evolution with time of biomass concentration. Points and dotted lines correspond to measured data for the three replicates. The solid line represents calculated values.
- Fig. 6. Variations of kinetic factors (F_D , F_A) and the thermodynamic factor (F_T) for nitrate reduction (Eq. 2) versus nitrate concentration
- Fig. 7. Variations of kinetic factors (F_D , F_A) and the thermodynamic factor (F_T) for nitrite reduction (Eq. 3) versus time
- Fig. 8. Nitrate and nitrite concentrations at the outlet of the column. Symbols represent experimental data and lines correspond to numerical simulation results.
- Fig. 9. Evolution of sulphate and chloride concentrations. Symbols represent Cl^- and SO_4^{2-} concentrations in the aqueous solution at the outlet. Dashed and dotted lines correspond to Cl^- and SO_4^{2-} concentrations in the solution at the inlet. The solid line represents calculated sulphate concentration at the outlet of the column.

Fig. 1

Fig. 2

Fig. 3

1000
1001
1002
1003

Fig. 4

Fig. 5

1009
1010
1011
1012

Fig. 6

Fig. 7

Fig. 8

Fig. 9

1029

Table 1: Chemical composition of the groundwater (in mmol kg⁻¹_{H2O})

Chemicals	pH	Eh (mV)	Alk	Ca	Mg	Na	K	Cl	NO ₃	SO ₄	Fe	DOC
Concentration	6.68	179	0.77	0.38	0.36	0.80	0.03	0.78	< LOQ	0.33	0.13	0.058

LOQ = Limit of Quantification

1030

1031

1032

1033

Table 2: Mineralogical composition of the aquifer formation

Minerals	Composition (in wt%)
Quartz	20-25
Chlorite	40-45
Mica / Illite	30-35
Pyrite	0.1
Plagioclases	5
Orthose	1
Smectite	0.5

1034

1035

1036

1037

Table 3 Chemical compositions and concentrations of the synthetic solutions

Concentration (mg L ⁻¹)		
Chemical species	Synthetic solution 1	Synthetic solution 2
Ca ²⁺	11.60	11.60
Mg ²⁺	11.40	8.60
K ⁺	1.10	1.10
Na ⁺	30.40	40.00
Cl ⁻	21.60	21.60
HCO ₃ ⁻	30.50	30.50
SO ₄ ²⁻	45.10	33.80
NO ₃ ⁻	50.00	50.00
CH ₃ COO ⁻	/	24.80

1038

1039

1040

1041

1042

1043