



Semi-analytical model of brine leakage through an abandoned plugged well to determine the Area of Review for CO₂ geological storages

Arnaud Réveillère, Jeremy Rohmer

► To cite this version:

Arnaud Réveillère, Jeremy Rohmer. Semi-analytical model of brine leakage through an abandoned plugged well to determine the Area of Review for CO₂ geological storages. EGU General Assembly 2012, Apr 2012, Vienne, Austria. hal-00658780

HAL Id: hal-00658780

<https://brgm.hal.science/hal-00658780>

Submitted on 18 Jun 2012

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.


L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Semi-analytical model of brine leakage through an abandoned plugged well to determine the Area of Review for CO₂ geological storages

Réveillère, A., Rohmer, J.


a.reveillere@brgm.fr



Abandoned wells review – context overview



- **Many CO₂ storage projects target deep saline aquifers located in sedimentary basins**
 - Possible historical oil & gas operations
 - Abandoned wells with sometimes unknown plugging records
- **By leaking through abandoned (plugged) wells, the saline brine risks to leak into overlying fresh water aquifers**
 - wells in the area where this is possible should be reviewed (“Area of review”)
 - This model enables to prioritize the areas to review supposing minimum plug parameters



Example in Alberta, Canada: 508 wells in a 30km x 30 km area.
from Bachu and Celia, 2009


Schematic layout of the model



> 1 active injection well

> 1 passive abandoned well, or « Leak »

- $z_c = z_{L-}$: wellbore only
- $z_c = z_{L+}$: porous column only
- $z_{L-} < z_c < z_{L+}$: plug & wellbore




- Drinking water
- Storage aq. brine
- Wellbore brine (vertical salinity gradient)

Beginning of CO₂ injection




- > Constant CO₂ injection flow rate starts (Q_0)



Brine leakage during CO₂ injection



- > Dense storage aquifer brine starts filling the leak up to z_l
- > The « wellbore brine » is pushed up
- > Pressure increases in the abandoned well




End of the CO₂ injection & « AoR »



> « Area of review » d_{AoR} :

Area where the pressure changes due to the injection can drive the reservoir brine up to a shallower aquifer of interest



- CO₂ plume
- Drinking water
- Storage aq. brine

Equations of the model



- > Static pressure equation in the abandoned well**
- > Pressure under the leak in the storage aquifer**
- > Pressure over the leak in the overlying aquifer**
- > Mass conservation**
- > Darcy flow in the cement plug**
- > Semi-analytical resolution**

Static pressure equation in the abandonned well




> Well bore pressure gradient

$$\nabla P = \nabla P_{grav} + \nabla P_{fric} + \nabla P_{acc}$$

- « frictional and inertial pressure gradients contributing typically a few percent or less.” (Pruess, 2006, for geothermal wells)

- $\rightarrow \nabla P = \nabla P_{grav}$


> Thermal equilibrium (Oldenburg & Rinaldi 2011)



$$P_{L-}^{static} - P_C^{static} = \Delta P_{cp}^0 + \Delta P_{cp}^1(z_I)$$

$$P_C^{static} - P_{L+}^{static} = \Delta P_{wb}^0 + \Delta P_{wb}^1(z_I)$$

Pressure under the leak in the storage aquifer




$$P_{L-}(t) - P_{L-}^0 = \frac{\mu_-}{4\pi k_- h_-} \left[Q_0 E_1 \left(\frac{d^2 S_-}{4T_- t} \right) - \int_0^t \frac{dQ_L}{dt'} E_1 \left(\frac{r_L^2 S_-}{4T_- (t - t')} \right) dt' \right]$$



Géosciences pour une Terre durable


brgm

Application to the « PICOREF » sector, Paris basin



P, T, X_S correspond to the Paris basin context as presented in Humez et al. (2011).


Brine density profile



Example of brine leakage




- CO₂ injection scenario: 1 Mt/y for 50 years
- D=6.7 km from the injection to the abandoned well
- Cement plug: 10 m high, weak permability of $10^{-13} m^2$



Area to review for a minimum cement plug height on permeability ratio




> CO₂ injection scenario: 1 Mt/y for 50 years



Prioritization of the wells to review



Adapted from Delmas et al., 2010



> Conclusions

- The model describes the leakage of brine through the leak. Compared to the state of the art (Nordbotten, Celia and co-authors, 2004-2009), it adds the possibility of accounting for density change within the leak due to the incoming of dense brine
- It shares the advantages (immediate computation) and drawbacks (homogeneous layers) of semi-analytical models
- Compared to a static approach (Nicot et al., 2009), this dynamic model enables less conservative estimation of the “Area of Review”, by including effects of cement plugs, of brine density differences and of leakage-induced pressure effects

> Next steps

- Inclusion of the CO₂ leakage
- Monte-Carlo analyses

> **Thanks!**

> **Acknowledgements**

- This work has been supported by the BRGM's Research project *CO₂ risks Management* integrated in the Research project CSCR03.

References



- Bachu, S., M.A. Celia. 2009. Assessing the potential for CO₂ leakage, particularly through wells, from geological, storage sites. *AGU 2008*
- Humez, P., Audigane, P., Lions, J., Chiaberge, C., Bellenfant, G., 2011. Modeling of CO₂ Leakage up Through an Abandoned Well from Deep Saline Aquifer to Shallow Fresh Groundwaters. *Transp Porous Med* (2011) 90:153–181.
- Nicot J.-P., Oldenburg, C., Bryant, S., Hovorka, S. (2009) Pressure perturbations from geologic carbon sequestration: Area-of-review boundaries and borehole leakage driving forces. *Energy Procedia* 1 (2009) 47-54
- Nordbotten, J. M., Celia, M. A. and Bachu, S., 2004. Analytical solutions for leakage rates through abandoned wells, *Water Resources Research* 40, W04204.
- Nordbotten, J.M., Kavetski, D., Celia, M.A. & Bachu, S. 2009, "Model for CO₂ Leakage Including Multiple Geological Layers and Multiple Leaky Wells", *Environmental science & technology*, vol. 43, no. 3, pp. 743-749.
- Pruess, K., 2006. Enhanced geothermal systems (EGS) using CO₂ as working fluid—A novel approach for generating renewable energy with simultaneous sequestration of carbon. *Geothermics* 35 (2006) 351–367