



HAL
open science

Intercomparison of Flow and Transport Models Applied to Vertical Drainage in Cropped Lysimeters

Michael Herbst, Wieslaw Fialkiewicz, Tao Chen, T. Pütz, Dominique Thiéry, Christophe Mouvet, Georges Vachaud, Harry Vereecken

► **To cite this version:**

Michael Herbst, Wieslaw Fialkiewicz, Tao Chen, T. Pütz, Dominique Thiéry, et al.. Intercomparison of Flow and Transport Models Applied to Vertical Drainage in Cropped Lysimeters. *Vadose Zone Journal*, 2005, 4 (2), pp. 240-254. 10.2136/vzj2004.0070 . hal-01061898

HAL Id: hal-01061898

<https://hal-brgm.archives-ouvertes.fr/hal-01061898>

Submitted on 8 Sep 2014

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

1
2
3
4
5
6
7
8 **Unsaturated methabenzthiazuron transport in a cropped lysimeter: comparison**
9 **between models and measurements**
10

11
12
13
14
15 M. Herbst*, W. Fialkiewicz, T. Chen, T. Pütz, D. Thiery, C. Mouvet,
16 G. Vachaud and H. Vereecken
17
18
19
20
21
22
23
24
25
26
27
28

29 Michael Herbst, m.herbst@fzjuelich.de
30 Thomas Pütz, t.puetz@fzjuelich.de
31 Harry Vereecken, h.vereecken@fzjuelich.de
32 ICG IV Institute of Agrosphere
33 FZJ Research Center Jülich
34 D- 52425 Jülich
35 Germany

36
37 Wieslav Fialkiewicz, w.fialkiewicz@brgm.fr
38 Dominique Thiery, d.thiery@brgm.fr
39 Christophe Mouvet, c.mouvet@brgm.fr
40 Bureau de Recherches Géologiques et Minières
41 BRGM
42 Avenue Claude Guillemin
43 F 45060 Orleans Cedex 02
44 France
45

46 Tao Chen, chen@hmg.inpg.fr
47 Georges Vachaud, georges.vachaud@hmg.inpg.fr
48 Laboratoire d'étude des Transferts en Hydrologie et Environnement
49 LTHE (UMR CNRS 5546, UJF, INPG, IRD)
50 BP53
51 38041 Grenoble cx09
52 France

1 **ABSTRACT**

2 The vertical water flow, heat flow and transport of the herbicide methabenzthiazuron were
3 monitored for 627 days in lysimeters sampled at a field site close to the research centre Jülich,
4 Germany. During this period the lysimeters were cropped with winter wheat, winter barley
5 and oat. The models TRACE, MARTHE, ANSWERS and MACRO were applied to the
6 lysimeter data with the scope of upscaling local scale process understanding for regional
7 scale. MARTHE and TRACE solve the 3-d Richards' equation for variably saturated water
8 flow. MACRO is a 1-d model based on the Richards' Equation and accounting for
9 preferential flow in the unsaturated zone, while ANSWERS is a regional scale capacity based
10 watershed model. Measurements of soil moisture, evapotranspiration, drainage, soil
11 temperature, pesticide residues and leaching are used for comparison with model results.
12 Although the adopted models differ in terms of model concepts, the use of model
13 performance indices proved a proper simulation of water flow for all models. The heat flow is
14 also well described with ANSWERS, MARTHE and MACRO. Larger deviations were found
15 between model results and measured pesticide transport. An inadequate reproduction of the
16 measured MBT degradation was found for the available model input parameters. A very small
17 amount of MBT leaching, observed in the measurements, was only reproduced with MACRO
18 after strong calibration. In other respects only plant parameters were calibrated. Calibration of
19 the crop conversion factor used for scaling of the potential evapotranspiration was found to be
20 a crucial parameter for the adequate description of the water balance by the models.

21

22 **INTRODUCTION**

23 During the last decades a significant increase of water bodies contaminated with pesticides
24 has been observed for various areas worldwide. Due to the use of aquifers for drinking water
25 supply, an assessment and a sound prediction of the impact of agricultural practice concerning

1 pesticide application is mandatory. In the framework of the EU-Project PEGASE (Pesticides
2 in European Groundwaters: detailed study of representative aquifers and simulation of
3 possible evolution scenarios) the test area 'Zwischenscholle' (20 km²), located 30 km west of
4 Cologne (Germany), was selected for a joint modelling on pesticide transport at regional scale
5 with four different modeling approaches. Two of these four models are MARTHE and
6 TRACE, which calculate water flow in variable saturated porous media using a generalized
7 Richards' equation. The other two models, MACRO and ANSWERS are used in a coupled
8 approach, linking both aforementioned unsaturated zone models with a groundwater flow
9 model. The validation of water flow and transport processes at regional scale is rather
10 difficult. Thus in a first step a lysimeter data set was chosen to check the modelling of water
11 flow and pesticide transport at local scale. Cropped lysimeters were used to monitor water
12 flow and fate of the pesticide methabenzthiazuron (MBT) for a period of almost two years.
13 The lysimeter station was located in the test area 'Zwischenscholle' and the lysimeter soil
14 approximates some of the soils found in the test area. The experimental data of the lysimeter
15 were supposed to validate the modelling of plant related processes, water flow and pesticide
16 transport in the unsaturated zone at local scale.

17 Large undisturbed lysimeters are a common experimental setup for investigations of pesticide
18 transport (Bergström, 1990; Boesten, 1994; Keller et al., 1995; Vink et al., 1997; Schoen et
19 al., 1999; Mikata et al., 2003), they are particularly applied for pesticide registration purposes.
20 The main advantages of lysimeters are the controlled boundary conditions and the
21 measurement of actual evapotranspiration, soil moisture and drainage for a large soil volume.
22 In addition the pesticide concentrations of the drainage water can be determined. The
23 representativeness of lysimeter observations for the field scale behaviour of transport
24 processes is still debated. Compared with field measurements with suction plates Jene et al.
25 (1997) measured 40% more bromide leaching in lysimeters. Comparative modeling of

1 pesticide transport has been the subject of several studies. Model comparisons on pesticide
2 transport have been carried out for lysimeters (Bergström and Jarvis, 1994; Vink et al., 1997;
3 Francaviglia et al., 2000) as well as for field studies (Pennel et al., 1993; Diekkrüger et al.
4 1995a; Armstrong et al., 2000; Gottesbüren et al. 2000; Tiktak, 2000; Vanclooster and
5 Boesten, 2000). The most recent and probably most extensive model comparison was
6 summarized by Vanclooster et al. (2000). The major outcome of this comparative pesticide
7 modelling on lysimeter and field data by Armstrong et al. (2000), Francaviglia et al. (2000),
8 Gottesbüren et al. (2000), Tiktak (2000) and Vanclooster and Boesten (2000) is what
9 Diekkrüger et al. (1995a) also stressed: The influence of the modellers' experience on model
10 results is large, probably larger than the influence of the selected model concept. Bergström
11 and Jarvis (1994) found very similar results for the five models included in their comparison.
12 They also note that, besides from taking the relevant processes into account, the identification
13 of correct model input parameters plays a key role in predicting pesticide transport.

14 Methabenzthiazuron is an effective herbicide in grain and certain vegetable crops. It is
15 classified as a rather persistent compound (Rouchaud et al. 1988) with a high sorptivity
16 (Diekkrüger et al., 1995b; Wüstemeyer, 2000).

17 MARTHE and TRACE are rather recent developments, based on the extension of codes
18 originally developed for the description of groundwater transport at regional scales. TRACE
19 comes from 3DFEMWATER (Yeh et al., 1992), which allowed to calculate both saturated
20 and unsaturated water flow. MACRO is a classical 1-dimensional model. Since the
21 introduction of MACRO it has already been used in several model comparison studies on
22 pesticide fate modelling (Bergström and Jarvis 1994; Diekkrüger et al. 1995a; Vink et al.
23 1997; Vanclooster et al., 2000), where it has proven a broad applicability to several pesticide
24 transport problems. During this study the version 5.0 is applied. ANSWERS is a capacity
25 based regional scale model for the vadose zone transport of solutes. It has already been

1 evaluated in the context of agricultural non-point source water quality models (Kosky and
2 Engel, 1997). The model concepts are rather contrasting (Table 1). MACRO is the only model
3 accounting for preferential flow and transport. Except for ANSWERS all models are based on
4 the Richards' equation for the calculation of soil water flow. MACRO and ANSWERS solve
5 the convection-dispersion equation (CDE) with a common numeric scheme, whereas TRACE
6 is coupled with 3dLEWASTE, which applies a hybrid Lagrangian/Eulerian method to solve
7 the CDE and MARTHE uses the total variation diminishing method. For pesticide
8 degradation only TRACE coupled with 3dLEWASTE uses a simple first-order kinetics
9 approach, whereas all the other models allow the use of a soil temperature and moisture
10 dependent biodegradation approach.

11 Basically, there are three main objectives: (i) to identify the crucial plant parameters and test
12 the applicability of the relevant plant data base, (ii) to check the model performances on water
13 flow and MBT transport and (iii) to compare the performance of the different model concepts.

14

15 **METHODS AND DATA**

16 **Experimental data**

17 Five undisturbed soil monoliths (free draining lysimeters) containing an Orthic Luvisol were
18 used to monitor the soil water balance. The sampling distance between the monoliths was
19 roughly 1 m. The monoliths were 1.1 m long and had a surface area of 1.0 m². Three
20 pedogenetic soil horizons were distinguished (Table 2). One of the lysimeters was treated
21 with a dose of 2.8 kg ha⁻¹ as TRIBUNIL[®] corresponding with an active ingredient application
22 of 248.11 mg m⁻² [phenyl-U-¹⁴C]methabenzthiazuron during the pre-emergence period of
23 winter wheat at the 25th of November 1988. The winter wheat (*Triticum Aestivum* L.) was
24 harvested and soil samples were taken with a hand auger at 3rd of August 1989 (252 days after

[®] Reg. Trademark, Bayer AG

1 application). In the following vegetation period winter barley (*Hordeum Vulgare* L.) was
 2 cropped and harvested on the 11th of May 1990. The next vegetation was oat, which was
 3 harvested at the 13th of August 1990, when a last soil sampling was carried out 627 days after
 4 the application.

5 From the 25th of November 1988 until the 13th of August 1990 the meteorological parameters
 6 precipitation, air humidity, air temperature, wind speed and radiation were monitored on a
 7 daily basis (Figure 1). Roughly every three days soil moisture was measured with a neutron
 8 probe. Leachate was collected on a three weekly basis. The amount of lysimeter drainage can
 9 be measured directly while the actual evapotranspiration Et_a (mm) was calculated from the
 10 soil water balance,

$$11 \quad Et_a = P - D - \Delta\theta \quad [1]$$

12 where P is the precipitation (mm), D is the drainage (mm) and $\Delta\theta$ is the change of soil
 13 moisture (mm) during the considered period of time.

14 MBT was extracted from the soil with acetone/ethyl acetate/chloroform. Using thin-layer
 15 chromatography the detection limit of ¹⁴C-labeled MBT was 0.67 $\mu\text{g l}^{-1}$.

16

17 **TRACE/3dLEWASTE**

18 TRACE (Vereecken et al., 1994) calculates the 3-dimensional unsaturated/saturated water
 19 flow in porous media. A modified Picard-iteration scheme (Celia et al., 1990) is applied in
 20 combination with a preconditioned conjugate gradient method in order to solve the following
 21 generalized 3-dimensional Richards' equation numerically,

$$22 \quad F_h \frac{\partial h(\vec{s}, t)}{\partial t} = \nabla(K(\vec{s}, h)\nabla H(\vec{s}, h)) + Q(\vec{s}, t) \quad \text{with} \quad F_h = \frac{\partial\theta}{\partial h} + S_h \quad [2]$$

23 where K is the hydraulic conductivity (LT^{-1}), \vec{s} is the position vector in a three dimensional
 24 space, h is the pressure head (L), H is the total head (L), Q is the source/sink term (T^{-1}), θ is

1 the soil water content (L^3L^{-3}), t is time (T), S_h is the specific storage coefficient (L^{-1}) and F_h is
 2 the specific water capacity (L^{-1}). For the spatial discretization hexahedral Galerkin-type finite
 3 elements are used. In order to take plant related processes into account the crop growth
 4 module SUCROS (Simplified and Universal Crop growth Simulation, Spitters et al., 1988) is
 5 implemented. In contrast to many other plant modules SUCROS estimates the assimilation
 6 rate from plant specific photosynthesis parameters and radiation. The calculated increase in
 7 biomass is used to predict leaf area growth and leaf area index (LAI), which is therefore not
 8 model input. The required plant data values can e.g. be found in van Heemst (1988). The crop
 9 coefficients (K_c -values) for the scaling of the reference evapotranspiration can be assigned for
 10 different seasonal stages according to the approach of Doorenbos and Pruitt (1978). Based on
 11 LAI the potential evapotranspiration is split into the fractions of potential evaporation and
 12 potential transpiration according to Beer's law. The actual transpiration is calculated from the
 13 potential transpiration in dependence of the pressure head according to the approach of
 14 Feddes et al. (1978). For the soil evaporation a flux boundary is applied to the uppermost
 15 element until the given pressure head h_{min} is reached (e.g. -10^{-4} cm). At this point TRACE
 16 switches to a fixed head boundary condition set to h_{min} .

17 3dLEWASTE (Yeh et al., 1992) is a hybrid Lagrangian-Eulerian finite element model of
 18 reactive solute transport through unsaturated/saturated media. 3dLEWASTE numerically
 19 solves the Lagrangian form of the convection-dispersion transport equation (CDE),

$$20 \quad \frac{DC}{Dt} + (\nabla \cdot \vec{V})C = \nabla \cdot \vec{D} \cdot \nabla C \quad [3]$$

21 where C is the solute concentration ($M L^{-3}$), DC/Dt is the material derivative of C with respect
 22 to time t , \vec{D} is the dispersion coefficient tensor ($L^2 T^{-1}$) and \vec{V} is the pore velocity vector
 23 ($L T^{-1}$) for the x,y and z direction. Here the advective term is solved in a mobile (Lagrangian)
 24 coordinate system using a single step reverse particle tracking, while the diffuse term is

1 solved in a fixed (Eulerian) coordinate system. A backward differencing scheme in time is
2 applied. A more detailed description of the hybrid Lagrangian-Eulerian approach can be
3 found at Yeh et al. 1992. For microbial decay a first order degradation rate coefficient is
4 applied to the sorbed and the liquid concentrations. A linear, Freundlich or Langmuir
5 isotherm can be applied for sorption. For the coupling between TRACE and 3dLEWASTE a
6 file is used containing the Darcy fluxes and the water contents for every finite element at
7 every time step. For simplicity the coupled model TRACE and 3dLEWASTE is referred to as
8 'TRACE' during the following text.

9

10 **ANSWERS**

11 The Areal Non-point Source Watershed Environmental Response Simulation, ANSWERS
12 (Bouraoui et al., 1997), is originally a watershed scale, diffuse pollution model for long term
13 simulation. The core of the system is a one-dimensional vertical model based on a capacity
14 approach for the soil water flux. A variable vertical segmentation is considered to account for
15 water movement through the soil profile. Infiltration into the uppermost layer is simulated by
16 the Green and Ampt equation (Green and Ampt, 1911). Soil water redistribution from upper
17 layer of soil to the root zone (discretized in 9 layers) is determined with the use of a Brooks
18 and Corey type equation (Brooks and Corey, 1964) on the basis of vertical downwards gravity
19 flow, with a hydraulic conductivity related to the average water content of the upper layer.
20 Similarly, percolation from root zone to the underlying unsaturated zone (drainage) is
21 determined with a hydraulic conductivity related to the average water content of the root zone.
22 The main parameters describing the hydraulic properties of the soil are the saturated hydraulic
23 conductivity K_s (cm h^{-1}), the porosity Φ ($\text{cm}^3 \text{cm}^{-3}$), the residual water content θ_r ($\text{cm}^3 \text{cm}^{-3}$),
24 the pore size distribution index λ_b (-), the bubbling pressure ψ_b (cm) and the field capacity F_c

1 (cm). They are obtained from soil texture and organic matter content with the Pedotransfer
2 functions of Rawls and Brakensiek (1989).

3 Soil evaporation and plant transpiration are modelled separately using Ritchie's equation
4 (Ritchie, 1972), where soil evaporation is related to the soil moisture of the upper layer and
5 the leaf area index LAI ($\text{m}^2 \text{m}^{-2}$). Plant transpiration is extracted from root zone assuming a
6 uniform root profile. The parameters describing the plant behaviour in terms of water uptake
7 and actual evapotranspiration are obtained from a database including 78 different types of
8 crop (Knisel, 1993). From sowing to harvest values of the LAI and root depth are given for
9 phenological stages.

10 The transport of solutes is calculated with the convection-dispersion equation. For sorption,
11 degradation and plant root uptake of pesticides the approach of ANSWERS is similar to
12 GLEAMS (Knisel, 1993). Two important assumptions are made: the degradation is only a
13 function of temperature (zero below 0°C and maximum at 25°C) and plant uptake is 10% of
14 water uptake. For the degradation of pesticides alternatively the equation of Graham-Bryce et
15 al. (1982) accounting for soil temperature and soil moisture dependent decay (Eq. 9) can be
16 used.

17

18 **MACRO**

19 MACRO 5.0 (Jarvis et al. 2004) is a one-dimensional dual-permeability model, operating at
20 the scale of a soil profile. The model accounts for preferential flow and transport in soil
21 macropores by dividing the soil pore system into two parts, one part with a high flow and low
22 storage capacity (macropores) and the remainder with a low flow and a high storage capacity
23 (micropores). The boundary between the pore regions is defined by the fixed pressure head C_{ten}
24 (L) having a corresponding water content θ_b ($\text{L}^3 \text{L}^{-3}$) and corresponding hydraulic conductivity

1 K_{mi} ($L T^{-1}$). The 1-dimensional form of the Richards equation is used to model flow in the
 2 micropores,

$$3 \quad F_h \frac{\partial h}{\partial h} = \frac{\partial}{\partial z} \left(K(z, h) \left(\frac{\partial h}{\partial z} + 1 \right) \right) - Q(z, t) \quad \text{with} \quad F_h = \frac{\partial \theta}{\partial h} \quad [4]$$

4 where z is the vertical coordinate (L). Eq. 4 is solved for finite differences using the implicit
 5 iterative procedure proposed by Celia et al. (1990). Soil water retention and unsaturated
 6 hydraulic conductivity are calculated using a modified form of the Mualem/van Genuchten
 7 approach (van Genuchten, 1980; Vogel et al., 2001) accounting for the macropore/micropore
 8 dichotomy by using the boundary pressure head partitioning the total porosity into micropores
 9 and macropores (Wilson et al., 1992; Mohanty et al., 1997). Flow in the macropores is calculated
 10 using the kinematic wave equation (Germann, 1985), assuming gravity-dominated flow (i.e.
 11 neglecting capillarity). The hydraulic conductivity function in the macropores is given as a
 12 simple power law expression of the macropore degree of saturation.

13 The one-dimensional convection-dispersion equation is applied for solute transport in the
 14 micropores,

$$15 \quad \frac{\partial (C\theta_m + (1 - f_{mac} - f_{ne})\rho_b S)}{\partial t} = \frac{\partial}{\partial z} \left(D\theta_m \frac{\partial C}{\partial z} - qC \right) - \sum U_i$$

16 [5]

17 where the source/sink term U_i ($M L^{-3} T^{-1}$) represents different processes like mass exchange
 18 between flow domains, kinetic sorption, solute uptake by the crop, biodegradation and lateral
 19 leaching losses to drains or groundwater. S is the sorbed concentration ($M L^{-3}$), f_{mac} is the mass
 20 fraction of solid material in contact with water in the macropores (-), f_{ne} is the fraction of the
 21 solid material providing non-equilibrium sorption (-), ρ_b is the soil bulk density ($M L^{-3}$), θ_m is the
 22 mobile water content ($L^3 L^{-3}$), q is the water flow ($L T^{-1}$) and D is the Dispersion coefficient (L^2
 23 T^{-1}). Transport in macropores is calculated neglecting dispersion-diffusion, but accounting for
 24 adsorption by the parameter f_{mac} (-) that partitions the sorption constant between the two flow

1 regions. Diffusive mass exchange between the two pore regions is calculated using approximate
 2 first-order equations based on an effective diffusion path length a_{scale} (L). Solute transport is
 3 solved by a Crank-Nicolson finite difference scheme utilizing an iterative, fully upstream
 4 weighting procedure with an empirical correction for numerical dispersion.

5 Root water uptake is calculated from evaporative demand, root distribution and soil moisture
 6 using a modified version of the approach developed by Feddes et al. (1978) accounting for
 7 water stress compensation (Jarvis, 1989). It is assumed, the crop can adjust to stress in one
 8 part of the root system by increasing uptake from other parts where the soil moisture
 9 conditions are more favourable. Root density is assumed to be distributed logarithmically
 10 with depth. Beer's law is used to partition the potential evapotranspiration into one fraction
 11 transpired by the canopy and the remaining fraction of evaporation from the soil. This is
 12 based on the green and on the total leaf area indices, given as a function of the day number in
 13 the year as user-specified input.

14 The heat conduction equation is solved using a standard Crank-Nicholson finite difference
 15 scheme. The effect of soil moisture and temperature on the first-order kinetics degradation of
 16 pesticides is estimated with the approach of Boesten and van der Linden (1991):

$$17 \quad \lambda = \lambda_{ref} \left(\frac{\theta}{\theta_{ref}} \right)^\beta e^{\alpha(T-T_{ref})} \quad \text{for} \quad T > 5^\circ\text{C} \quad [6]$$

18 where λ is the degradation rate coefficient (d^{-1}), λ_{ref} is the reference rate coefficient (d^{-1}), θ_{ref} is
 19 the reference water content (cm cm^{-3}), T is the soil temperature ($^\circ\text{C}$), T_{ref} is the reference
 20 temperature ($^\circ\text{C}$), and α ($^\circ\text{C}^{-1}$) and β (-) are empirical parameters. The pesticide uptake by
 21 roots is modelled as a function of root water uptake and pesticide concentration. An empirical
 22 concentration factor is used to define the fraction of pesticide concentration taken up by the
 23 roots.

24

1 **MARTHE**

2 MARTHE (Modelling Aquifers with Rectangular cells, Transport and hydrodynamics) was
3 originally developed as a 3-dimensional groundwater model designed to compute water flow
4 and solute transport in saturated porous media (Thiéry, 1995). Additional routines allow the
5 computation of unsaturated flow, thus MARTHE also solves the 3-dimensional form of the
6 Richards equation numerically. The spatial discretization is based on finite differences. The
7 resulting matrix equation is iteratively solved using conjugate gradients combined with
8 Choleski pre-conditioning. Advective, diffusive and dispersive transport can be simulated
9 using three different techniques: CDE based on finite differences, Total Variation
10 Diminishing and Method of Characteristics.

11 The main features of the plant module are very similar to MACRO. The evolution of the LAI
12 is a function of main development stages (i.e. germination, maturity and harvest). Like for
13 MACRO an exponential function is used to divide the potential evapotranspiration into
14 transpiration and evaporation. Canopy interception is not considered. For the root system
15 development of crops a linear growth from germination until maturity is assumed. Between
16 maturity and harvest the specified maximum root depth remains constant. The root density
17 can be calculated from several functions. During this study an exponentially decreasing root
18 density was assumed. For the estimation of the actual transpiration the reduction according to
19 the water stress compensation concept (Jarvis 1989) is taken into account.

20 The root uptake of solutes is simply calculated from a solution uptake factor (-) describing the
21 fraction of mass lost to root uptake by plants. Concerning solute degradation a sequential
22 first-order decay, a temperature and soil moisture dependent first-order decay or a simple
23 first-order decay can be taken into account. For the soil temperature and moisture dependent
24 first-order decay a parameterized Graham-Bryce approach (Graham-Bryce, 1982) or the
25 concept of Boesten and van der Linden (1991) can be used.

1

2 **Model input**

3 The functional relation between pressure head, soil water content and unsaturated hydraulic
 4 conductivity plays a key role for the modeling of water flow (Vereecken and Kaiser 1999;
 5 Herbst et al., 2002). For MARTHE and TRACE the soil water retention function of van
 6 Genuchten (1980) with parameter $m=1$ was used, which is equivalent to the equation
 7 proposed by Brutsaert (1966),

$$8 \quad \theta(h) = \theta_r + \frac{\theta_s - \theta_r}{1 + (\alpha|h|)^n} \quad [7]$$

9 where θ denotes the water content ($\text{cm}^3 \text{cm}^{-3}$), h is the pressure head (cm), θ_r is the residual
 10 water content ($\text{cm}^3 \text{cm}^{-3}$), θ_s is the water content at saturation ($\text{cm}^3 \text{cm}^{-3}$), α is the inverse of
 11 the bubbling pressure (cm^{-1}) and the dimensionless shape parameter n (-).

12 By using $m=1$ instead of $m=1-1/n$ the closed analytical expression of the Mualem/van
 13 Genuchten approach (van Genuchten, 1980) for the $K(h)$ function is lost. Therefore the
 14 unsaturated hydraulic conductivity function of Gardner (1958) was applied,

$$15 \quad K(h) = \frac{K_s}{1 + (b|h|)^c} \quad [8]$$

16 where K is the unsaturated hydraulic conductivity (cm d^{-1}), K_s is the saturated hydraulic
 17 conductivity (cm d^{-1}), and b (cm^{-1}) and c (-) are empirical parameters. The soil hydraulic
 18 properties listed in Table 4 were determined by Vereecken and Kaiser (1999). They derived
 19 the soil hydraulic properties from the soil properties listed in Table 2 with the Pedotransfer
 20 functions (PTF) of Vereecken et al. (1989 and 1990) and fitted the θ_r and α values. TRACE
 21 and MARTHE allow for the use of the modified Mualem/van Genuchten approach described
 22 above, while MACRO is based on the common Mualem/van Genuchten approach (with $m=1-$
 23 $1/n$) modified for the dual porosity approach (Wilson et al., 1992; Mohanty et al., 1997; Vogel

1 et al., 2001). In order to obtain comparable soil hydraulic functions for the Richards' equation
 2 based models the retention and unsaturated hydraulic conductivity functions for MACRO
 3 (Mualem/van Genuchten, $m=1-1/n$) were derived in a two step procedure. First θ_r , θ_s , α , n and
 4 K_s were fitted to the already available functions of Vereecken and Kaiser (1999) using the least
 5 squares procedure of RETC (van Genuchten, 1991). In a second step the parameters defining the
 6 macropore system the saturated matrix conductivity K_{mi} (cm d^{-1}), the diffusion path length a_{scale}
 7 (cm) and the boundary pressure head C_{ten} (cm) were calibrated on the measured MBT
 8 concentrations in the drainage water (Table 4). For ANSWERS soil hydraulic parameters like
 9 K_s and field capacity were calculated internally with the PTF of Rawls and Brakensiek (1989)
 10 from the properties given in Table 2. The use of other soil hydraulic functions is not very
 11 appropriate, since the capacity based approach implemented in ANSWERS is closely linked
 12 to the PTFs of Rawls and Brakensiek (1989). The initial values of soil moisture or pressure
 13 head for the model start were derived from the neutron probe measurements.

14 All the models can handle a linear, Freundlich or Langmuir sorption isotherm. For all of the
 15 models the sorption of MBT was described with a linear sorption isotherm. The values of the
 16 distribution coefficient K_d ($\text{cm}^3 \text{g}^{-1}$) are calculated from a partition coefficient K_{oc} of 527 cm^3
 17 g^{-1} , found in the Agritox database (<http://www.inra.fr/agritox>), and the organic matter content
 18 assuming $K_d=K_{oc} f_{oc}$. The resulting K_d for the three soil horizons from top to the bottom is
 19 5.27, 2.11 and $1.58 \text{ cm}^3 \text{g}^{-1}$ respectively. Thus the retardation factor for the top horizon at
 20 water saturation is 21.2, indicating a high sorption of MBT. For MARTHE and ANSWERS a
 21 temperature and soil moisture dependent degradation based on the equation of Graham-Bryce
 22 et al. (1982) is taken into account,

$$23 \quad \lambda(T, M) = e^{[\alpha + b \cdot \ln(M) + (g \cdot T^{-1})]} \quad [9]$$

1 where λ is the degradation rate (d^{-1}), T is the soil temperature ($^{\circ}\text{K}$), M is the gravimetric soil
 2 moisture (%) and a (-), b (-) and g ($^{\circ}\text{K}$) are parameters. From batch experiments Wüstemeyer
 3 (2000) found the following parameters related to MBT:

$$4 \quad \ln(\lambda) = 7.0 + 1.343 \cdot \ln(M) - 4476 \cdot T^{-1} \quad [10]$$

5 From which the half-life (DT_{50}) can be calculated as follows:

$$6 \quad \text{DT}_{50}(T, M) = \frac{\ln(2)}{\lambda(T, M)} \quad [11]$$

7 3dLEWASTE does not account for temperature or soil moisture dependent degradation. For
 8 this case a first order kinetic decay with a DT_{50} of 200d was found after calibration. By using
 9 the mean of the measured soil temperature at 10 cm depth ($\overline{T}_{10} = 10.3^{\circ}\text{C}$) and the mean of the
 10 measured soil moisture at 25 cm depth ($\overline{\theta}_{25} = 0.22$) a DT_{50} for reference conditions ($T_{\text{ref}} = 20^{\circ}\text{C}$
 11 and $\theta_{\text{ref}} = 0.39$) of 162 days was calculated according to the approach of Boesten and van der
 12 Linden (1991). This DT_{50} is applied for MACRO. Figure 2 shows a comparison of the
 13 Graham-Bryce approach with the Boesten and van der Linden approach. It is clearly visible,
 14 that the Boesten and van der Linden approach with a reference DT_{50} of 162 days gives higher
 15 half-lives than the Graham-Bryce approach. Thus the remaining mass of MBT in soil should
 16 be smaller for MARTHE and ANSWERS applying the Graham-Bryce approach than for
 17 MACRO and TRACE, where the DT_{50} is generally higher. For all the models the degradation
 18 rate for sorbed and dissolved MBT is supposed to be the same. The dispersion length was
 19 assumed to be 1.7 cm for all of the models.

20 MACRO, MARTHE and ANSWERS calculate the soil temperature from daily mean air
 21 temperature by solving the equation of heat diffusion and convection. For MARTHE the
 22 mineral thermal conductivity is set to $1.5 \text{ W m}^{-1} \text{ }^{\circ}\text{C}^{-1}$, water thermal conductivity is set to 0.6
 23 $\text{W m}^{-1} \text{ }^{\circ}\text{C}^{-1}$, mineral volumetric specific heat is set to $2 \cdot 10^6 \text{ J m}^{-3} \text{ }^{\circ}\text{C}^{-1}$ and water specific heat

1 is set to $4185 \text{ J kg}^{-1} \text{ }^\circ\text{C}^{-1}$. MACRO applies the approach of Jansson (1991) to estimate thermal
 2 conductivity and volumetric heat capacity from the soil properties summarized in Table 2.

3 The potential reference evapotranspiration ET_p (Figure 1) was calculated according to the
 4 approach of Penman/Monteith (Monteith, 1975). Potential evapotranspiration and
 5 precipitation are applied as the upper boundary condition, whereas a seepage face is applied to
 6 the lower boundary at the bottom of the lysimeter. The seepage face boundary is characterized
 7 by a no-flow boundary for unsaturated conditions:

$$8 \quad q(z,t) = 0 \quad \text{for} \quad h < 0 \quad [12]$$

9 If the seepage face becomes saturated, the boundary turns into a prescribed head boundary
 10 with $h(z,t)=0$. The vertical lysimeter wall is set as a no-flow boundary condition.

11 For MACRO, MARTHE and TRACE the spatial discretization consists of 110 elements of 1
 12 cm thickness each. The 3-d models MARTHE and TRACE are run in a 1-d mode. Due to the
 13 infiltration approach according to Green and Ampt (1911) the spatial discretization for
 14 ANSWERS requires a thickness of 40 cm for the uppermost element. The eight elements
 15 beneath have a thickness of 8.75 cm each.

16

17 **Validation criteria**

18 A commonly used criterion for model validation is the root mean square error (RMSE), where
 19 the root of the mean squared residuals is calculated. The RMSE has the unit of the considered
 20 variable. The squared residuals are also used for the second criterion applied, which is the
 21 coefficient of model efficiency CME (Nash and Sutcliffe, 1970). Here they are used to
 22 determine the proportion of the deviation from the observed mean, which can be explained by
 23 the model,

$$CME = \frac{\sum_{i=1}^n (x_o(t) - x_{omean})^2_i - \sum_{i=1}^n (x_o(t) - x_s(t))^2_i}{\sum_{i=1}^n (x_o(t) - x_{omean})^2_i} \quad [13]$$

where x_o is the observed value, x_s is the simulation result at time t and x_{omean} is the arithmetic mean of the observed values. The CME is a dimensionless criterion that can have negative values. The highest value possible is 1, indicating that observation and model are completely in agreement. The Index of Agreement IA (Willmott, 1981) is also dimensionless and ranges between 0 and 1:

$$IA = 1 - \frac{\sum_{i=1}^n (x_o(t) - x_s(t))^2_i}{\sum_{i=1}^n (|x_o(t) - x_{omean}| + |x_s(t) - x_{omean}|)^2_i} \quad [14]$$

Because CME and IA are dimensionless, they can be used to compare the model quality between different variables, while the RMSE gives an idea about the model error in the units of the variable under consideration.

11

12 RESULTS

13 Water flow

14 One aim of this study was to identify the crucial parameters of plant related processes
 15 concerning the pesticide transport in soil. During the calibration process of the four models
 16 three crucial parameters were identified: The leaf area index LAI, the root depth Rd and the
 17 crop conversion factor K_c . Table 3 summarizes the calibrated and the original maximum
 18 values of this three parameters. Only for MACRO the maximum LAI was slightly modified
 19 during calibration. For all the crops the emergence and harvest dates were known, thus the
 20 uncertainty concerning the LAI development was rather small and modifications of the LAI
 21 did not improve model results significantly. A quite large variability of the maximum LAI
 22 was detected for the different plant databases. The difference between MACRO and

1 MARTHE, which are based on the same plant database, and ANSWERS is larger than the
2 difference between the three crops. Compared to the plant database LAIs the LAI estimated
3 with TRACE for oat is much smaller. The LAI estimated for winter wheat and winter barley
4 are much more similar. The root depth defines the zone of the soil, where the sink term of
5 transpiration influences the soil moisture. Differences between calibrated and uncalibrated
6 maximum Rd range between 5 and 40 cm, for MACRO and ANSWERS respectively. The
7 crop conversion factor K_c determines the amount of ET_p . Among this three plant parameters
8 the K_c has probably the largest influence on the model results and the largest differences
9 between calibrated and uncalibrated plant parameters can be detected for the this parameter.
10 The variation of the calibrated maximum K_c for different crops is large (Table 3). The lowest
11 K_c was found for the winter barley, while the highest values were assigned to winter wheat.
12 With ANSWERS the LAI and K_c factors were unchanged during calibration. For TRACE and
13 MACRO the Rd and K_c -values were significantly modified during the calibration procedure.
14 The same basically holds true for MARTHE, but the K_c was changed more moderately. For
15 MARTHE a constant K_c was applied for every crop, without any temporal variability
16 according to phonological stages.

17 The total water balance (Table 6) is well reproduced by all models. ANSWERS slightly
18 overestimates the total amount of actual evapotranspiration ET_a , whereas the other models
19 slightly underestimate the total ET_a . The relative errors for single water balance components
20 are small, except for the change in soil moisture, which is merely a result of the small
21 absolute amount of change in soil moisture.

22 Apart from the overall water balance, the reproduction of the temporal evolution of the water
23 balance components is relevant. Figure 3 shows a comparison between observed and
24 modelled cumulative actual evapotranspiration. In general the four models match the
25 measurements, which exhibit only small standard deviations, except for the two drying

1 periods with high evapotranspiration demands. During the first spring period (1989) all the
2 models applied slightly underestimate the amount of actual evapotranspiration. This is vice
3 versa for the second period (spring 1990), when MARTHE shows an increase in actual
4 evapotranspiration too early and too low. ANSWERS reproduces this increase too early and
5 in total too high. The calculation of the coefficient of model efficiency (CME) with the mean
6 of the measured actual evapotranspiration and the corresponding model results reveals that
7 ANSWERS, MACRO and MARTHE are close to each other in their ability to reproduce
8 evapotranspiration while TRACE shows the highest CME (Table 5). For the models the ratio
9 between cumulative actual evapotranspiration (ET_a) and cumulative potential
10 evapotranspiration (ET_p) differs for several periods. The K_c -values applied already indicate
11 this. Combined with the different reduction methods to estimate ET_a from ET_p for the
12 different models the ratio between ET_a and ET_p shows large deviations. For example at the
13 end of the first drying period during summer 1989 at the same day the ratio ET_a/ET_p ranges
14 between 0.65 and 1.0, for TRACE and MARTHE respectively, whereas the resulting ET_a is
15 quite similar for all models (Figure 3).

16 A comparison of calculated and observed volumetric soil moisture at two depths is shown in
17 Figure 4. For the depth of 25 cm the first significant deviations occur during the drying period
18 of spring 1989. During this period TRACE reproduces the drying quite accurately, whereas
19 ANSWERS, MACRO and MARTHE exhibit a slightly delayed drying of the soil. During the
20 following wetting period in the autumn and winter 1989 ANSWERS slightly overestimates
21 the re-wetting while TRACE and MARTHE slightly underestimate the re-wetting. For this re-
22 wetting period MACRO is in good agreement with the measurements. Large deviations
23 between measurements and model results in the upper layer can be observed during the
24 second drying period of spring 1990 for ANSWERS and MARTHE. In this case ANSWERS
25 predicts the drying too early while MARTHE underestimates the drying. MACRO

1 underestimates the drying even more than MARTHE. Generally, for the depth of 25 cm all
2 the models are basically in accordance to the measurements, which is supported by the CME
3 ranging between 0.65 and 0.93 for MACRO and TRACE respectively (Table 5). For the depth
4 of 85 cm the results of TRACE and MARTHE are very close to each other. Both models
5 show much too high soil water contents during spring and summer 1989, although the
6 measurements show a high standard deviation during the summer 1989 when the soil was
7 very dry. In the following vegetation period (spring and summer 1990) the results of both
8 models match the measurements. During this second period the effect of drying is much less
9 pronounced. In contrast to this ANSWERS reproduces the decrease in soil moisture during
10 spring and summer 1989 much better than TRACE and MARTHE. Large deviations for
11 ANSWERS can be found for the second vegetation period where ANSWERS clearly
12 underestimates the soil moisture. For the soil moisture of the lower layer the best performing
13 model is MACRO with an IA of 0.96. Although the models show a quite different behaviour
14 for the soil moisture at 85 cm depth the CME are quite close to each other varying between
15 0.70 and 0.86. The IA is ranging even smaller, varying between 0.92 and 0.96.

16 In relation to the mean the standard deviation of the measured drainage is clearly higher than
17 the standard deviation of the measured evapotranspiration. Figure 5 shows the comparison
18 between modelled and measured cumulative drainage. During winter 1988/1989 the highest
19 amount of drainage was measured. MACRO and TRACE underestimate this amount, while
20 the amount estimated with ANSWERS is very close to the measurement. During the second
21 period of drainage (winter 1989/1990) compared to the measurements the results of
22 ANSWERS show a delay, but the amount of drainage is well reproduced, while TRACE
23 clearly overestimates the amount of drainage. MARTHE shows the best agreement with the
24 drainage measurements with the highest CME of all models. Concerning drainage MACRO
25 shows a CME of 0.81, although for this lysimeter experiment there is a tendency to slightly

1 underestimate the amount of drainage water. The temporal course of drainage is well
2 reproduced.

3

4 **Transport of Methabenzthiazuron**

5 In the models MARTHE, MACRO and ANSWERS degradation is soil moisture and
6 temperature dependent. Figure 6 shows a comparison between the model results concerning
7 soil temperature at 10 cm depth. This depth was chosen because the measured soil
8 temperature at 10 cm depth exhibits a high amplitude, which is a result of being close to the
9 soil surface, where the soil heat flux is mainly driven by the atmospheric conditions.
10 Furthermore most of the degradation takes place in the uppermost soil layer with high organic
11 matter content. The modelled soil temperatures of MARTHE, MACRO and ANSWERS are
12 very close to each other and they are close to the measurements. The temporal variability of
13 soil temperature is well reproduced by the models, which is supported by the small RMSE
14 (Table 5). For MARTHE, MACRO and ANSWERS the degradation was calculated with the
15 modelled soil temperature and soil moisture. Figure 7a reveals that 252 days after application
16 the remaining total MBT mass was found in the upper 10 cm. This observation is generally
17 reproduced with TRACE, MACRO and MARTHE, although the three models show a small
18 amount of MBT in the soil layer between 10 and 20 cm depth. The amount of MBT in the
19 upper 10 cm estimated with MARTHE is very close to the measurement while TRACE
20 clearly overestimates the remaining mass of MBT. Related to the applied mass, TRACE
21 estimated 12 % too much. MACRO also clearly overestimates the MBT residues for the first
22 sampling date. With ANSWERS no MBT is found in the upper compartment (0-40 cm depth).
23 The total mass of MBT is found in the depth between 40 and 70 cm. Related to the applied
24 mass, the total mass left in the profile according to ANSWERS is 13.6 % too much.

1 After 627 days the measurements show that the total mass left in the profile is just little lower
2 than after 252 days and it is divided into the two uppermost layers (0-20 cm). Compared to
3 the measurements the results obtained with MACRO and TRACE are the closest (Figure 7b).
4 MACRO and TRACE underestimate the amount of MBT, but they reproduce the right depth.
5 MARTHE also reproduces the right depth, but the degradation of MBT is clearly
6 overestimated. The same holds for ANSWERS and additionally the mass is again estimated
7 deeper in the profile than measured.

8 As assumed from Figure 2 the estimated mass of MBT residuals is higher for both sampling
9 dates for MACRO and TRACE than for MARTHE and ANSWERS. This is an effect of the
10 higher DT_{50} . For TRACE the DT_{50} is constantly 200 days, while MACRO modifies the DT_{50}
11 of 162 days according to soil moisture and temperature following the approach of Boesten
12 and van der Linden (1991). MARTHE and ANSWERS compute smaller DT_{50} from the
13 Graham-Bryce equations (Eq. 10 and 11). For the first sampling date 252 days after
14 application the RMSE calculated for the 11 depths (see Figure 7) is 30.8, 3.9, 9.7 and 11.7, for
15 ANSWERS, MARTHE, TRACE and MACRO respectively. For the second sampling 627 days
16 after application the RMSE for the 11 depths is 13.7, 10.1, 5.1 and 6.4, respectively. The
17 models applied with a higher DT_{50} (TRACE and MACRO) reproduce the measurements of
18 the second date better than the ones of the first date. This is vice versa for MARTHE, which is
19 based on the Graham-Bryce approach. MARTHE reproduced the measurements of the first
20 sampling better than for the second sampling.

21 According to Figure 8 the measured concentrations of MBT in the drainage water show a
22 small peak roughly 100 days after application. The total mass of MBT lost by leaching during
23 the experimental period is $14.6 \mu\text{g m}^{-2}$, equivalent to 0.0059 % of the applied mass of MBT.
24 None of the models predicts MBT in drainage water, except the calibrated MACRO estimates
25 at total amount of MBT leaching of $7.8 \mu\text{g m}^{-2}$. MACRO was mainly calibrated on the

1 macropore parameters listed in Table 4. Figure 8 shows that the peak of MBT leaching
2 predicted with MACRO is a little delayed, and the total amount of MBT leaching is
3 underestimated. Apart from the calibration of the macropore parameters with the water
4 balance components the fraction of sorption sites in the macropores was calibrated with the
5 measured MBT leaching, f_{mac} was set to 0.005 (-), which corresponds to the small macropore
6 volume fraction ($\theta_s - \theta_b$, Table 4).

7

8 **DISCUSSION**

9 Three crucial parameters were identified during the calibration procedure. The calibration of
10 the LAI was moderate, probably due to the exactly known emergence and harvest dates. A
11 striking point is the higher variability between different plant databases than between
12 calibrated and uncalibrated model parameters. A query at the plant parameter database
13 (PlaPaDa, Breuer and Frede, 2003) revealed LAIs between 2.3 and 4.6 for winter wheat. This
14 shows the variability of this parameter for different environmental conditions, and it might
15 indicate that the model functions are adapted to the related plant database. Like the LAI the
16 root depths were rather moderately calibrated, except for the root depth of oat. For this crop
17 three of the four modellers increased the root depth. From the calibration of LAI and root
18 depth it could be assumed that the chosen databases of Knisel (1993), Van Heemst (1988) and
19 FOCUS (2000) in combination with the chosen model are generally applicable to the
20 Zwischenscholle test site. The really important plant parameter is the crop conversion factor
21 K_c . This parameter has a strong influence on the overall water balance. Except for ANSWERS
22 all models were calibrated on K_c for each of the crops. For winter wheat and oat the K_c values
23 were increased, while for winter barley K_c was decreased. The decrease of the K_c for winter
24 barley was required to account for the effect of a plant disease keeping the barley from a
25 normal plant development. Against this background and having in mind the amount of

1 calibration of K_c even for this parameter the selected databases are basically applicable for the
2 Zwischenscholle. But care should be taken not to underestimate the actual evapotranspiration
3 by using K_c values that are too small. This can only be checked in terms of the water balance.
4 Further there might be, compared to the field situation, generally a slightly higher
5 evapotranspiration for lysimeters. Bergström and Jarvis (1994) and Boesten (1994) attribute
6 this to the 'oasis effect', i.e. the lysimeters are partially surrounded by hard surfaces without
7 any evaporation, which presumably causes in combination with wind a lateral flow of dry air
8 over the lysimeters, thereby increasing the evapotranspiration of the lysimeters.

9 As expected the soil moisture near the soil surface is clearly influenced by evapotranspiration.
10 This is reflected in the model results. If the model correctly reproduces the amount of
11 transpiration and evaporation the soil moisture at the depth of 25cm is well described.
12 Supported by the CME and IA all the model results for evapotranspiration and soil moisture
13 at 25 cm depth are clearly acceptable, which is basically the result of well described plant
14 related processes from the calibration of plant parameters. The soil moisture at the depth of
15 85cm is influenced by root water uptake and drainage. Even for the soil moisture at 85 cm a
16 proper reproduction can be stated for all the models (Table 5), whereas the temporal course of
17 drainage is reproduced with different quality. According to Nash and Sutcliffe (1970) a model
18 with CME lower than 0.5 should be rejected. With a CME of 0.1 ANSWERS is below this
19 threshold and even TRACE is quite close to this value having a CME of 0.58. The use of a
20 criterion like the CME is supposed to support the validation of models by bringing in an
21 objective component, but it is still the model user to decide whether a model should be
22 rejected or not. The IA for the drainage estimated with ANSWERS and TRACE, 0.67 and
23 0.89 respectively, is in an acceptable range. The total amount of drainage estimated by
24 ANSWERS and TRACE is close to the measurements. And Figure 5 also reveals, that the
25 variation of drainage with time is generally reproduced. Thus the modelling of drainage with

1 ANSWERS and TRACE is still acceptable, although this variable is not as well reproduced as
2 the other water flow variables. It would be expected that the drainage flow could be well
3 described, if also the soil moisture close to the lower boundary of the lysimeter is well
4 described. This is true for MARTHE and MACRO, but not for ANSWERS and TRACE.
5 According to the validation criteria TRACE reproduces the soil moisture at 85cm even
6 slightly better than MARTHE. But the drainage is described significantly better by
7 MARTHE. The validation criteria for the soil moisture at 85cm calculated with ANSWERS
8 are in the same range for all the models, while the drainage is not that well reproduced. For
9 ANSWERS this effect might be attributed to the capacity based approach for water flow,
10 because the estimation of the drainage is not completely consistent with the lower boundary
11 condition of the lysimeter experiment.

12 In contrast to the water flow the modelling of the fate of MBT is rather problematic.
13 MARTHE, ANSWERS and MACRO account for a soil temperature and moisture dependency
14 of degradation. The model variables soil temperature and soil moisture near the surface are
15 well described (Table 5), whereas the degradation of MBT is not that well described. It seems
16 like the modelling of soil moisture and temperature is easier than the quantification of the
17 relation between degradation and soil moisture/temperature. Basically the models can be
18 divided into two groups. One group is TRACE and MACRO using a long half-life and
19 predicting the long-term behaviour correctly. The other group is MARTHE and ANSWERS
20 using a clearly shorter half-life and predicting the amount of MBT residues of the first
21 sampling date (252 days after application) correctly but for the last sampling (627 days after
22 application) the residues are underestimated. Probably the first order kinetics approach
23 applied for all models is not suitable to describe the degradation of MBT (Diekkrüger et al.
24 1995b). The first order kinetics approach might be appropriate to describe the short-term
25 behaviour of the MBT degradation, but the long-term behaviour might be influenced by a

1 very slow sorption/desorption kinetic. Then a hockey stick degradation function might be
2 more appropriate. A validation of this statement from the data used in this study is limited,
3 because a longer monitoring with more sampling dates would be required. This would also be
4 necessary to decide if the moisture and temperature dependent first order decay is superior to
5 the simple first order decay. The degradation rates of MBT in literature vary between 30 days
6 (Rouchaud et al., 1988), 139 days (Jarvis, 1995) and 172 days (Wüstemeyer, 2000) under
7 field conditions. This might be another hint to a slow sorption/desorption kinetic for the long–
8 term behaviour of MBT.

9 A leaching of 0.0059 % of the applied mass of MBT occurs. This process can be described
10 with MACRO only after calibration. Without the calibration of the macropore soil hydraulic
11 properties and the fraction of sorption sites in the macropores no leaching was estimated with
12 MACRO. This contributes to the findings of Bergström and Jarvis (1994), where only after
13 calibration the pesticide leaching due to preferential flow is well described. For registration
14 purposes in Europe a leaching level of 0.1% or more of the applied dose is relevant
15 (Vanclooster et al., 2000). From this point of view the small amount of MBT leaching is not
16 relevant, nevertheless there is a small lack of transport process description detected for
17 TRACE, ANSWERS and MARTHE.

18 For the reproduction of evapotranspiration, soil moisture and drainage basically all model
19 concepts are suitable. For the description of degradation the performance of the simple first
20 order kinetics is comparable to the temperature and soil moisture dependent first order
21 concepts. Here a more extensive data set on MBT residues will probably reveal the better
22 performance of the more sophisticated approach taking soil moisture and temperature into
23 account. Further improvement of the description of degradation might be possible with a
24 nested first order approach allowing for different half-lives for the short-term and the long-
25 term behaviour of pesticide degradation. The biggest conceptual constraint concerning

1 pesticide fate was detected for ANSWERS. Due to the thickness of the uppermost element,
2 necessary for the Green and Ampt infiltration, the transport of the pesticide cannot be
3 described if the downward movement of the compound is very small. The center of mass
4 predicted with ANSWERS is always much too deep in the profile. And degradation and
5 sorption occur usually very close to the surface, which cannot be described properly with
6 ANSWERS. The other conceptual constraint can be detected for MARTHE, TRACE and
7 ANSWERS. These models are unable to describe preferential flow, which must be seen
8 against the background of the difficult parameter identification. The problem of the derivation
9 of macropore parameters will increase with scale and a process can only be taken into account
10 if also the parameters are available.

11 The use of five parallel lysimeters revealed a high variability of measured drainage amounts,
12 while the evapotranspiration is rather similar. The cores were sampled quite close to each
13 other (~ 1m), indicating that the spatial variability of soil properties is high. Even the use of
14 five parallel lysimeters involves still a large uncertainty concerning the field scale drainage
15 amount. Thus the lysimeter concept is probably not able to capture the field scale
16 heterogeneity of processes strongly influenced by the spatial variability of soil properties.

17

18 **CONCLUSIONS**

19 During the calibration of plant parameters three crucial parameters were identified: the LAI,
20 the root depth and the crop conversion factor. Among these parameters the crop conversion
21 factor values were changed significantly during calibration. For most cases the K_c was
22 increased which is seen as a result of the lysimeter set up for the measurement of the actual
23 evapotranspiration. Generally the selected databases of plant parameters are applicable to the
24 'Zwischenscholle' test area.

1 Having in mind that only the plant parameter values were calibrated, the water flow is well
2 described with all the model concepts, which is proved by the calculated validation criteria.
3 The fate of MBT is not as well described as the water flow. The residues of MBT are
4 estimated for the right depth with MACRO, MARTHE and TRACE. But the amounts of MBT
5 residues are only poorly reproduced. Laboratory measured soil moisture and temperature
6 dependent half-life does not improve the modeling of degradation significantly. More
7 extensive data on MBT residues would be needed to verify a slow sorption/desorption kinetic,
8 which also calls the first order approach applied for all model used in this study into question.
9 A very small amount of MBT leaching can be described with MACRO, but only after
10 extensive calibration.

11 Basically all the model concepts are well applicable for water flow. The amount of
12 preferential flow not considered with TRACE, ANSWERS and MARTHE is not significant for
13 the water flow but for the MBT leaching. A conceptual limitation was found for the capacity
14 based ANSWERS. Here the Green and Ampt equation for infiltration requires a very thick
15 uppermost element hindering the sound estimation of transport and degradation of MBT close
16 to the surface.

17

18 **ACKNOWLEDGEMENT**

19 The authors acknowledge financial support by the EU within the framework of PEGASE,
20 contract EVK1-CT1999-00028.

21

22

1 REFERENCES

- 2
- 3 Armstrong, A., K. Aden, N. Amraoui, B. Diekkrüger, N. Jarvis, C. Mouvet, P. Nicolls and C.
4 Wittwer. 2000. Comparison of pesticide leaching models: results using the Brimstone
5 Farm data set. *Agricultural Water Management* 44:153-181.
- 6 Bergström, L. 1990. Use of lysimeters to estimate leaching of pesticides in agricultural soils.
7 *Environmental Pollution* 67:325-347.
- 8 Bergström, L.F. and N.J. Jarvis. 1994. Evaluation and comparison of pesticide leaching
9 models for registration purposes. *J. Environm. Sci. Health* 29:1061-1072.
- 10 Boesten, J.J.T.I. and A.M.A van der Linden. 1991. Modelling the influence of sorption and
11 transformation on pesticide leaching and persistence. *Journal of Environmental Quality*
12 29: 917-925.
- 13 Boesten, J.J.T.I. 1994. Simulation of bentazon leaching in sandy soil from Mellby (Sweden)
14 with the PESTLA model. *Journal of Environmental Science and Health, Part A* 29:1231-
15 1253
- 16 Bouraoui, F., G. Vachaud, R. Haverkamp and B. Normand. 1997. A distributed physical
17 approach for surface-subsurface water transport modeling in agricultural watersheds. *J. of*
18 *Hydrology* 203:79-92.
- 19 Breuer, L. and H. Frede. 2003. PlaPaDa – an online plant parameter data drill for
20 eco-hydrological modelling approaches. ([http://www.uni-giessen.de/~gh1461/plapada/
21 plapada.html](http://www.uni-giessen.de/~gh1461/plapada/plapada.html)).
- 22 Brooks, R.H. and Corey, A.T. 1964. Hydraulic Properties of Porous Media. *Hydrology Paper*
23 No. 3. Colorado State Univ., Fort Collins. Colorado.
- 24 Brutsaert, W. 1966. Probability laws for poresize distributions. *Soil Science* 101:85-92.

- 1 Celia, M.A., E.T. Bouloutas and R.L. Zarba. 1990. A general mass-conservative numerical
2 solution for the unsaturated flow equation, *Water Resour. Res.* 26(7): 1483-1496.
- 3 Diekkrüger, B., D. Söndgerath, K.C. Kersebaum and C.W. McVoy. 1995a. Validity of
4 agroecosystem models, a comparison of results of different models applied to the same
5 data set. *Ecological modelling* 81:3-29.
- 6 Diekkrüger, B. , P. Nörtshäuser and O. Richter. 1995b. Modeling pesticide dynamics of a
7 loam site using HERBSIM and SIMULAT. *Ecological Modelling* 81:111-119.
- 8 Doorenbos, J and W.O. Pruitt. 1977. *Crop Water Requirements*. FAO. Irrigation and Drainage
9 Paper 24. Rome, Italy.
- 10 Feddes, R.A., P.J. Kowalijk and H. Zaradny. 1978. Simulation of field water use and crop
11 yield. *Simulation Monographs, PUDOC*. Wageningen. The Netherlands. 189 pp.
- 12 FOCUS, 2000. 'FOCUS groundwater scenarios in the EU review of active substances'.
13 Report of the FOCUS groundwater scenario workgroup. EC Document Reference
14 SANCO/321/2000 rev.2. 202 pp. (<http://arno.ei.jrc.it/focus/gw>).
- 15 Francaviglia, R., E. Capri, M. Klein, J. Hosang, K. Aden, M. Trevisan and G. Errera. 2000.
16 Comparing and evaluating pesticide leaching models: results for the Tor Mancina data set
17 (Italy), *Agricultural Water Management* 44:135-151.
- 18 Gardner, W.R. 1958. Some steady state solutions of the unsaturated moisture flow equation
19 with application to evaporation from a water table. *Soil Science* 85:228-232.
- 20 Germann, P. 1985. Kinematic wave approach to infiltration and drainage into and from soil
21 macropores. *Transactions of the ASAE* 28:745-749.
- 22 Gottesbüren, B., K. Aden, I. Bärlund, C. Brown, M. Dust, G. Görlitz, N. Jarvis, S. Rekolainen
23 and H. Schäfer. 2000. Comparison of pesticide leaching models: results using the
24 Weiherbach data set. *Agricultural Water Management* 44:153-181.

- 1 Graham-Bryce, I.J., P.H Nicholls, R.J. Baker, R.J. Hance, S.J. Embling and D. Hill, 1982.
2 Movement of fluometuron and ^{36}Cl in soil under field conditions: Computer simulations.
3 Weed Res. 22:271-283.
- 4 Green, W.H. and G.A. Ampt. 1911. Studies in soil physics. I. The flow of air and water
5 through soils. J. Agr. Sci. 4:1-24.
- 6 Herbst, M. and B. Diekkrüger. 2002. The influence of the spatial structure of soil properties
7 on water balance modeling in a microscale catchment, Physics and Chemistry of the Earth
8 27:701-710.
- 9 Jansson, P.E. 1991. Simulation model for soil water and heat conditions. Description of the
10 SOIL model. Report 165, Div. of Agric. Hydrotechn., Dept. Soil Sci., Swedish Univ.
11 Agric. Sci.72 pp. Uppsala
- 12 Jarvis, N.J. 1989. A simple empirical model of root water uptake. Journal of Hydrology
13 105:57-72.
- 14 Jarvis, N.J., 1995. Simulation of soil water dynamics and herbicide persistence in a silt loam
15 soil using the MACRO model. Ecological Modelling 81:97-109.
- 16 Jarvis, N.J. ,XXXX. 2004 .Macro5.0 XXXXXXXX , submitted to Vadose Zone Journal
- 17 Jene, B., G. Fent and R. Kubiak. 1997. Comparison of lysimeters to the actual field situation
18 with regard to the movement of soil water and a ^{14}C -labelled herbicide and bromide. The
19 environmental fate of Xenobiotics (eds. Del Re, A.A.M., E. Capri, P. Evans and M.
20 Trevisan). 179-186.
- 21 Keller, K.E. and J.B. Weber. 1995. Mobility and Dissipation of ^{14}C -labeled atrazine,
22 Metolachlor, and Primisulfuron in undisturbed field lysimeters of a coastal plain soil. J.
23 Agric. Food Chem. 43:1067-1086
- 24 Knisel, W.G. (Ed.). 1993. GLEAMS Groundwater loading effects of agricultural management
25 systems, Version 2.10. Dept. Publication No. 5. Biological & Agricultural Engineering

- 1 Department, University of Georgia Coastal Plain Experimental Station. Tifton. 260 pp.
2 http://www.cpes.peachnet.edu/sewrl/Gleams/gleams_y2k_update.htm
- 3 Kosky, K.M. and B.A. Engel. 1997. Evaluation of three distributed parameter
4 hydrologic/water quality models. ASAE Paper No. 97-21010. In the mini-conference on
5 applications of emerging technologies in hydrology. (eds. Ward, A.D. and B.N. Wilson).
6 ASAE. St. Joseph. MI.
- 7 Mikata, K., F. Schnöder, C. Braunwarth, K. Ohta and S. Tashiro. 2003. Mobility and
8 degradation of the herbicide imazosulfuron in lysimeters under field conditions. *J. Agric.*
9 *Food Chem.* 51:177-182.
- 10 Mohanty, B., R.S. Bowman, J.M.H. Hendrickx and M.T. van Genuchten. 1997. New
11 piecewise-continuous hydraulic functions for modelling preferential flow in an
12 intermittent flood-irrigated field. *Water Resources Research* 33: 2049-2063
- 13 Monteith, J. L. 1975. *Vegetation and the atmosphere.* 439 pp. Academic Press.
- 14 Nash, J.E and J.V. Sutcliffe. 1970. River flow forecasting through conceptual models: Part I –
15 A discussion of principles. *Journal of Hydrology* 10:282-290.
- 16 Rawls, W.J. and D.L. Brakensiek. 1989. Estimation of soil retention and hydraulic
17 properties. *In: Unsaturated Flow in Hydrologic Modeling: Theory and Practice*, H.J.
18 Morel-Seytoux (Eds.). NATO ASI series c 275: 275-300. Kluwer Acad. Press.
- 19 Rouchaud, J, P. Roucourt, M. Van Himme, F. Benoit, N. Ceustermans, J. Gillet, W. Plumier
20 and G. Vulsteke. 1988. Metabolism of methabenzthiazuron in the soil of pea crops. *J.*
21 *Agric. Food. Chem.* 36:642-645
- 22 Pennel, K.D., A.G. Hornby, R.E. Jessup and P.S.C. Rao. 1993. Evaluation of five simulation
23 models for predicting aldicarb and bromide under field conditions. *Water Resources Res.*
24 26(11):2679-2693.
- 25 Ritchie, J.T. 1972. Model for predicting evaporation from a row crop with incomplete cover.

- 1 Water Resour. Res. 8:1204-1213.
- 2 Schoen, R., J.P. Gaudet and T. Bariac. 1999. Preferential flow and solute transport in a large
3 lysimeter, under controlled boundary conditions. *Journal of Hydrology* 215:70-81.
- 4 Spitters, C.J.T., H. van Keulen and H. van Kraalingen. 1988. A simple but universal crop
5 growth simulation model, SUCROS87. *In* R. Rabbinge, H. Van Laar & Ward (ed),
6 Simulation and system management in crop protection. Simulation Monographs. PUDOC,
7 Wageningen.
- 8 Thiéry, D. 1995. Modélisation 3D du transport de masse avec le logiciel MARTHE, version
9 5.4. BRGM report, R 38149 HYT/DR 95, 171 pp. Orleans.
- 10 Tiktak, A. 2000. Application of pesticide simulation models to the Vredepeel dataset II
11 Pesticide fate. *Agricultural Water Management* 44:119-134.
- 12 Vanclooster, M. and J.J.T.I. Boesten. 2000. Application of pesticide simulation models to the
13 Vredepeel dataset I. Water, solute and heat transport. *Agricultural Water Management*
14 44:105-117.
- 15 Vanclooster, M., J.J.T.I. Boesten, M. Trevisan, C.D. Brown, E. Capri, O.M. Eklo, B.
16 Gottesbüren, V. Gouy and A.M.A. van der Linden. 2000. A European test of pesticide-
17 leaching models: methodology and major recommendations. *Agricultural Water*
18 *Management* 44:1-19.
- 19 Van Genuchten, M.Th. 1980. A closed form equation for predicting the hydraulic
20 conductivity of unsaturated soils. *Soil Sci. Soc. of Am. J.* 44: 892-898.
- 21 Van Genuchten, M.Th., F.J. Leij and S.R. Yates. 1991. The RETC Code for Quantifying the
22 Hydraulic Functions of Unsaturated Soils. U.S. Salinity Laboratory EPA/600/2-91/065. 85
23 pp. Riverside. California.

- 1 Van Heemst, H.D.J. 1988. Plant data values required for simple crop growth simulation
2 models: review and bibliography, Simulation Report CABO-TT nr. 17. Wageningen.
- 3 Vereecken, H., J. Feyen, J. Maes and P. Darius.1989. Estimating the soil moisture retention
4 characteristic from texture, bulk density and carbon content, Soil Science 148:389-403.
- 5 Vereecken, H., J. Maes and J. Feyen. 1990: Estimating unsaturated hydraulic conductivity
6 from easily measured soil properties, Soil Science, 149:1-12.
- 7 Vereecken, H., G. Lindenmayr, O. Neuendorf, U. Döring and R. Seidemann. 1994. TRACE
8 A mathematical model for reactive transport in 3D variably saturated porous media,
9 Internal Report KFA-ICG-4-501494, Jülich.
- 10 Vereecken, H. and R. Kaiser. 1999. Analysis of multi-step outflow data and pedotransfer
11 functions to characterise soil water and solute transport at different scales. In M. Th. van
12 Genuchten, F.J. Leij and L. Wu (ed.) Characterization and measurement of the hydraulic
13 properties of unsaturated porous media, part 2. Riverside, California, 1089-1102.
- 14 Vink, J.P.M., B. Gottesbüren, B. Diekkrüger and S.E.A.T.M. van der Zee. 1997. Simulation
15 and model comparison of unsaturated movement of pesticides from a large clay lysimeter.
16 Ecological Modelling 105:113-127.
- 17 Vogel, T., M.T. van Genuchten and M. Cislérova. 2001. Effect of the shape of the soil
18 hydraulic functions near saturation on variably-saturated flow predictions. Advances in
19 Water Resources 24:133-144.
- 20 Willmott, C.J. 1981. On the validation of models. Physical Geography 2.
- 21 Wilson, G.V., P.M. Jardine, and J.P. Gwo. 1992. Modeling the hydraulic properties of a
22 multiregion soil. Soil Science Society of America Journal 56:1731-1737.
- 23 Wüstemeyer, A. 2000. Abbau und Transport von Ethidimuron und Methabenzthiazuron in
24 einer Parabraunerde-Beitrag zur Validierung des Lysimeterkonzepts. PhD Thesis. Jülich,

1 Germany

2 Yeh, G.T., P. Sharp-Hansen, B. Lester, R. Strobl and J. Scarbrough. 1992.
3 3DFEMWATER/3DLEWASTE: Numerical codes for delineating wellhead protection
4 areas in agricultural regions based on the assimilative capacity criterion, U.S.
5 Environmental Protection Agency, GA 30613, Athens.

6

1 FIGURE CAPTIONS

2

3 Fig. 1. Measured atmospheric conditions and calculated reference evapotranspiration during
4 the experimental period.

5 Fig. 2. Isoline plot of soil temperature and moisture dependent DT_{50} for MBT calculated
6 according to Graham-Bryce (Wüstemeyer, 2000) and according to Boesten and van der
7 Linden (1991), with reference $DT_{50}=162$ d, $\theta_{ref}=0.39$ cm³ cm⁻³, $\alpha=0.01$ K⁻¹, $\beta=0.2$ and
8 $T_{ref}=20^{\circ}\text{C}$ (Eq. 6). Volumetric water content was transformed to gravimetric with the topsoil
9 bulk density of 1.57 g cm⁻².

10 Fig. 3. Measured and predicted actual evapotranspiration (cumulative). Bars are standard
11 deviations of measurements.

12 Fig. 4. Measured and predicted soil moisture at two depths. Bars are standard deviations of
13 measurements.

14 Fig. 5. Measured and predicted drainage (cumulative). Bars are standard deviations of
15 measurements.

16 Fig. 6. Measured and predicted soil temperature at 10 cm depth.

17 Fig. 7. Measured and predicted MBT residues (applied MBT = 100%) 252 days (a) and 627
18 days (b) after application.

19 Fig. 8. Accumulated mass of measured MBT in drainage water and model results