



HAL
open science

Physico-chemical exchanges and transfer of pollution in aquifers

J. Rochon, Dominique Thiéry

► **To cite this version:**

J. Rochon, Dominique Thiéry. Physico-chemical exchanges and transfer of pollution in aquifers. Flow and transport in porous media : Euromech 143, 1981, Delft, Netherlands. pp.213-219. hal-01062358

HAL Id: hal-01062358

<https://brgm.hal.science/hal-01062358>

Submitted on 9 Sep 2014

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Physico-chemical exchanges and transfer of pollution in aquifers

J. ROCHON & D. THIERY

Bureau de Recherches Géologiques et Minières, Orléans, France

1 INTRODUCTION

This paper is divided into two parts. The first one is a mathematical analysis of different laws for physic and chemical exchanges occurring during a natural flow in an aquifer. The second part shows, with field experiments at Bonnaud (Jura), how it is possible to determine the parameters of an exchange law in order to forecast the long term evolution of the concentration of a solute which has reached the aquifer.

2 INTRODUCTION TO THE FIRST PART

This part will deal with the study of the concentrations in the water of an aquifer after an injection of tracer. The hypothesis relative to the aquifer are :

- homogeneous and isotropic aquifer,
- uniform and permanent flow.

The evolution of the concentration will result of three phenomenous :

- advection : it is displacement of the tracer with the flow,
- dispersion,
- physic and chemical exchanges between phase.

It is assumed that there are no exchanges with the lower and upper boundaries of the aquifer. The general equation is :

$$\frac{\partial C}{\partial t} = D \frac{\partial^2 C}{\partial x^2} - u \frac{\partial C}{\partial x} - \frac{1-n}{n} \frac{\partial S}{\partial t}$$

with the relation

$$\frac{\partial S}{\partial t} = f(C, S)$$

- C = concentration in the liquid phase (water)
- S = concentration in the solid phase (aquifer)
- D = dispersion coefficient
- n = kinematic porosity
- u = effective velocity

t = time

x = distance

Many exchanges laws may be studied : an exchange law may be reversible or not, its equilibrium equation (or "isotherm") may be linear or not (e.g. Langmuir scheme), see J. Rochon 1978.

We choose to study some of these laws which seem to be the most useful.

2.1. Linear exchanges with linear exchange kinetic

$$\frac{\partial C}{\partial t} = D \frac{\partial^2 C}{\partial x^2} - u \frac{\partial C}{\partial x} - \frac{1-n}{n} k_c (k_e C - S)$$

$$\frac{\partial S}{\partial t} = k_c (k_e C - S)$$

which may be written with dimensionless variables :

$$\frac{\partial C_A}{\partial t_R} = D \frac{\partial^2 C_A}{\partial x_R^2} - \frac{\partial C_A}{\partial x_R} - C_A \cdot N_e (C_R - S_R)$$

$$\frac{\partial S_R}{\partial t_R} = N_e (C_R - S_R)$$

with

$$x_R = x/L \quad t_R = t / \frac{L}{u}$$

$$C_R = C \cdot L \cdot n / m \quad S_R = S \cdot k_e \cdot L \cdot n / m$$


Three dimensionless numbers appears :

$Pe = \frac{uL}{D}$ it is the Peclet number


$N_e = \frac{L \cdot k_c}{u}$ it is the number of Exchanges during the advection along the distance L

$C_A = \frac{1-n}{n} k_e$ it is the Exchange Capacity of the aquifer

This system of two dimensionless differential equations has been solved by finite differences with B.R.G.M. numerical code M.O.D.E.L. (J. Ausseur, B. Kanehiro, J.P. Sauty, 1979) and made it possible to design dimensionless type curves describing the



Graph 1. Linear exchanges : influence of the Number of exchange $Ca = 1$



Graph 2. Linear exchanges : influence of the Number of exchange $Ca = 2$

evolution of concentrations following a slug injection of tracer. The calculations have been performed for a Peclet number equal to 10, a number of exchange ranging from 0.1 to 10 and a Retention Capacity from 0.1 to 5. Graphs 1 and 2 shows the type curves for $Ca = 1$ and $Ca = 2$.

2.2. Exchanges according to Langmuir isotherm

The equilibrium equation is :

$$S_e = \frac{k_d C}{1 + C/C_d}$$

with

C_d = half saturation concentration in the liquid phase (water)

S_e = equilibrium concentration in the solid phase (aquifer)

The exchange kinetic is of second order :

$$\frac{\partial S}{\partial t} = k_c \left(k_e C - \frac{S_e - S}{S_e} \right)$$

The transformation of the variable is the same as in the previous chapter. The dimensionless equation may be written :

$$\frac{\partial C_R}{\partial t_R} = \frac{1}{Pe} \cdot \frac{\partial C_R}{\partial x_R} - C_a \cdot Ne \left(C_R - S_R - \frac{C_R S_R}{S_a} \right)$$

$$\frac{\partial S_R}{\partial t_R} = Ne \left(C_R - S_R - \frac{C_R S_R}{S_a} \right)$$

with a fourth dimensionless number

$$S_a = \frac{C_d \cdot L \cdot n}{m}$$

it is the Saturation Constant.

if S_a is equal to infinity which means no saturation effect, the system of equations is similar to the system describing the linear exchanges.

As the solution depends on four dimensionless numbers, it is not possible to draw a set of type curves.


We choose to draw type curves for instantaneous exchanges corresponding to Ne equal to infinity.

If the Peclet number is determined, only two dimensionless number are left : Ca and S_a . Type curves have been drawn to study the influence of each of these numbers. See graphs 3 and 4.


2.3. Ionian exchanges

The hypothesis are the following :

- the sum of the cations in the liquid phase is T ,
- the sum of the cations in the solid phase is Q_0 ,
- the anions are not adsorbed by the solid phase,
- the total quantity of injected cations is m .



Graph 3. Influence of the Saturation Constant



Graph 4. Influence of the Retention Capacity

The relation between phases is the following :

$$S_e = \frac{k Q_0 C}{T_0 (k-1) C}$$

when the equilibrium is reached or at any time, if the exchange kinetic is instantaneous. k is the constant of the mass action law.

The sum of all the cations in solution was equal to T_0 . At the time of injection, it is increased at the injection point and then is described by the law of dispersion without exchanges :

$$\frac{\partial T}{\partial t} = D \frac{\partial^2 T}{\partial x^2} - u \frac{\partial T}{\partial x}$$

The reason is that the anions are not adsorbed which is an hypothesis, so the sum of the anions in solution is not involved in exchanges. The electrical neutrality tells that the sum T of the cation too will not be involved in exchanges (see J. Rochon, 1979).

Assuming that the exchange kinetic is instantaneous, it is possible to derive the following equilibrium relation which holds at any time

$$S = \frac{k_a C}{T_R + C/c_d}$$

with the following transformations :

$$T_R = T/T_0$$

$$k_e = k Q_0 / T_0$$

$$C_d = T_0 / (k-1)$$

The equilibrium relation has the same expression than Langmuir one, when T_R is equal to unity, i.e. for low concentrations of injection.

The dimensionless system of differential equations is :

$$\frac{\partial C_R}{\partial t_R} = \frac{1}{P_e} \frac{\partial^2 C_R}{\partial x_R^2} - \frac{\partial C_R}{\partial x_R} - \frac{C_a}{(T_R + C_R/S_e)} \left(T_R \frac{\partial C_R}{\partial t_R} - C_R \frac{\partial T_R}{\partial t_R} \right)$$

$$\frac{\partial T_R}{\partial t_R} = \frac{1}{P_e} \frac{\partial^2 T_R}{\partial x_R^2} - \frac{\partial T_R}{\partial x_R}$$

when $C_0 \ll T_0$, $T_R = 1$ and is constant, and these equations are similar to Langmuir scheme. However the second equation which has no exchanges term shows that the variation of T is much faster than the variation of C . After a time equal to about twice the advection time the evolution of concentrations is identical to Langmuir scheme.


3 INTRODUCTION TO THE SECOND PART

All the tracer experiments in uniform flow which are analysed in this part took place in 1974 at Bonnaud, near Lons-le-Saunier (Jura - France). The experiments were designed together by two teams : the Bureau de Recherches Géologiques et Minières (BRGM) and the Section d'Application des Radio-éléments du Commissariat à l'Energie Atomique (SAR-CEA). The aim of the research was to study extensively with field experiments the underground migration of various matters soluble in water. All the results are described in B. Gaillard, J. Guizerix, J. Margat, J. Molinari, P. Peaudecarf, 1976.

3.1 Description of the experiment field


The aquifer has the following characteristics :

- the water table is of limited thickness (3 to 4 m) which helps for the measurements,
- the aquifer is confined which implies no influences of the fluctuation of the water table and no exchanges with the non saturated zone,
- the aquifer is not thick and is well defined,
- the naturel variations of level are small,
- the hydraulic conductivity is high which helps the advection of the injected tracers (transmissivity : $10^{-3} \text{ m}^2/\text{s}$)



Graph 5. Longitudinal and transversal geological cross-sections of aquifer

In order to get a uniform gradient and increase the velocities to keep the experiment duration reasonable, a uniform flow has been imposed and controlled by a set of injection wells (M) and pumping wells (N) with constant rates (see graph 6).



Graph 6. Situation of wells

3.2 The field experiment to be analysed

Among all the experiments three of them have been selected and are analysed in the following lines. Each injection took place in well C and measurements were in well D, 13 meters further. The main characteristics of these experiments are gathered in table 1.

Table 1. Main characteristics of the field experiments at Bonnaud

Injected matter	I-Na	Rhodamine WT	Uranine
	Mass injected (g)	20	4
Date of injection	23/10/74	18/10/74	25/10/74
Uniform flow $10^{-3} \text{ m}^3/\text{s}$	3.39	2.42	2.36
Incidents	36 hours stop		
Maximum concentration measured $\mu\text{g}/\text{l}$	295	17	105
Estimation of residual concentration (from previous experiments $\mu\text{g}/\text{l}$)	40	4	6

3.3 Method of interpretation

The three experiments have been analysed separately by adjustment of the parameter with a mathematical model. The number of parameter is 4 : D , u , k_c , k_e and also the cross-section area of the part of the aquifer in which the migration takes place.

Other experiments with "perfect" tracers like tritium for which there are no exchanges have been performed on the same experiment field. The analysis of these experiments (P. Peaudecerf, J.P. Sauty, 1978) made it possible to determine the parameters describing advection and diffusion :

- effective velocity $u = 3.8 \cdot 10^{-5}$ m/s (3,3 m/day),
- (kinematic porosity $n = 33 \%$),
- diffusion coefficient $D = 2,5 \cdot 10^{-5}$ m²/s (2.2 m²/day).

These parameters lead to a dispersivity $\alpha = D/u = 0.66$ m and a Peclet number : $Pe = uL/D = 19.8$ ($L = \text{distance} = 13$ m).

This high value of Peclet number shows that the advection term is much larger than the diffusion one.

The experiments with the other matters (I-Na, Rhodamine WT, Uranine) have been analysed with these same values for D , u and n . The analysis have been done only by adjusting the parameters of exchanges between phases.

3.3.1. Choice of the model of exchange

Various injections have been realised on the same location with the same tracers but with different injected mass (ratio of 10). None of these test show any mass effect ; in other words, for a given tracer, and after a given duration the concentration is proportionnal to the injected mass of tracer. Moreover, as the capacity of cationic exchange Q_0 of the aquifer and the chemical nature of the water T_0 are not known, it has not been possible to try any interpretation with ionian exchange scheme or Langmuir scheme. The model which has been chosen is then the reversible and linear exchanges. It must be noted that, as the duration of the measurements is sometimes short and as some incidents occur during the experiments, it should have been illusory to use a more complicated model with more parameters.

3.3.2. Determination of the parameter

For each experiment two parameters have been determined :

- the kinetic constant k_c (corresponding to the half exchange time : $t_{1/2} = \ln 2 / k_c$),
- the equilibrium constant k_e .

The corresponding dimensionless parameters are :

- number of exchanges : $Ne = L \cdot k_c / u$
- retention capacity : $Ca = k_e (1-n) / n$

The interpretation scheme is one dimensional so the transverse diffusion is neglected. The flow is assumed to take place in a prism of aquifer of section A (thickness h and width l) in which the concentration is uniform. The thickness of the aquifer ranges between 2.9 m at injection point to 2.5 m

at measurement point. The width l is not known. It is possible to compute it by the ratio of the injected mass to the initial injected concentration which is a parameter of the model.

The parameters obtained after calibration are gathered in table 2.

Table 2. Parameters of exchange

	I-Na	Rhodamine WT	Uranine
kinetic constant k_c (10^{-6} s^{-1})	3.0	8.0	7.5
half exchange time t_d (days)	2.7	1.0	1.1
equilibrium constant k_e	0.22	1.12	1.49
number of exchan- ges Ne	1.03	2.74	2.57
Retention capa- city Ca	0.45	2.27	3.03
equivalent width of prism l (m)	6.7	8.4	6.7

The comparison of the measured and computed concentration appear on graph 7 to 9. These graphs show that the calibration is reasonable, keeping in mind the incidents which occur during the experiments and also the fact that the concentration measurements seems sometimes affected by erratic variations.

3.4. Interpretation of the exchange parameters


The experiment with Sodium Iodide (I-Na) shows little exchange because the Retention Capacity is small ($Ca = 0,45$) and the kinetic of exchange is slow ($Ne = 1.0$).

The experiments with Rhodamine and Uranine give results which are quite similar (see graph 8 and 9) with much more exchanges : the Retention capacity ranges from 2 to 3, the Number of Exchanges is equal to about 2.5. The computed width of the equivalent prism of aquifer is equal to 7 or 8 meters for the 3 experiments. This width does not describe the lateral extension of the plume of tracer but rather the width of aquifer influenced by the pumping at the measurement point D.


4 CONCLUSION

The use of models makes it possible to predict the migration of a pollution in the water of an aquifer, taking into account the physic and chemical interactions of the aquifer. To determine the exchange parameters it is necessary to do the following :


- perform a first experiment on the field



Graph 7. Sodium Iodide



Graph 8. Uranine



Graph 9. Rhodamine WT - Tracer injection at Bonnaud (Jura)

with a "good" tracer (i.e. with no or little exchanges) in order to determine the parameters describing advection and dispersion, perform a second test -preferably a field experiment- with a solute similar to the product to study but which is not a pollutant. When such an experiment may not be performed (for economical reasons or because there is no solute with properties similar to the pollutant to study) a dynamic test may be realised in laboratory with a sample of the ground and with the pollutant. From this second experiment, the exchange parameters will be deducted. However a laboratory test will only give a rough estimation of the parameters by not taking into account the heterogeneity of the real field.

NOTATIONS

C = Concentration in the liquid phase
 C_a = Retention Capacity
 C_e = Equilibrium Concentration
 C_R = Dimensionless Concentration in the liquid phase
 C_d = Half-saturation Concentration (kg/m^3)
 D = Dispersion Coefficient
 k = Equilibrium Constant
 k_c = Kinetic of exchange constant
 k_e = Equilibrium Constant
 L = Distance between injection point and measurement point
 m = Injected mass of solute or quantity of injected cations
 n = Kinematic porosity of the aquifer
 N_e = Number of exchanges
 P_e = Peclet Number = uL/D
 Q_o = Sum of the cations in the solid phase
 S = Concentration in the solid phase
 S_a = Saturation Constant
 S_R = Dimensionless Concentration in the solid phase
 T_o = Sum of the cations initially in the liquid phase
 T = Sum of the cations in the solid phase
 t = Time
 t_R = Dimensionless time
 u = Effective velocity or poral velocity
 x = Distance (m)
 x_R = Dimensionless Distance

BIBLIOGRAPHY

- Ausseur, J.Y., Kanehiro, B., Sauty, J.P. Mass transfer through fractured rocks "M.O.D.E.L." Code. Convection Dispersion Exchange Decay, Bureau de Recherches Géologiques et Minières, rapport n° 79 SGN 748 HYD (to be printed)
- Gaillard, B., Guizerix, J., Margat, J., Molinari, J., Peaudecerf, P., 1976, Action thématique programmée "hydrogéologie", Etude des caractéristiques de transfert de substances chimiques dans les nappes (site de Bonnaud - Jura), Bureau de Recherches Géologiques et Minières, rapports 75 SGN 056 AME, 76 SGN 235 AME, 76 SGN 236 AME, 76 SGN 240 AME, 76 SGN 226 AME.
- Peaudecerf, P., Sauty, J.P. 1978, Application of a mathematical model to the characterisation of dispersion effects on groundwater quality, Prog. Wat. Tech., vol. 10 n° 5/6, pp 443-454, Pergamon Press
- Rochon, J. 1978, Propagation de substances miscibles en interaction physico-chimique avec le substrat, Approche simplifiée pour l'utilisation en hydrogéologie, Thèse de Doc. Ing., Institut National Polytechnique de Grenoble, 25 janvier 1978.
- Rochon, J. 1979, Echange cationique au cours d'un écoulement unidirectionnel en milieu poreux saturé, in : "workshop OCDE/NEA", L'utilisation des matériaux argileux pour l'isolation des déchets radioactifs, Paris, 10-12 septembre 1979.
- Villiermaux, J., Van Swaaij, W.P.M. 1969, Modèle représentatif de la distribution des temps de séjour dans un réacteur semi-infini à dispersion axiale avec zones stagnantes, Application à l'écoulement ruisselant dans des colonnes d'anneaux Raschig, Chemical Engineering Science, Vol. 24.