



**HAL**  
open science

## **Influence of dissolved oxygen on the bioleaching efficiency of a mesophile to moderate thermophile consortium under oxygen enriched atmosphere**

Anne-Gwenaëlle Guezennec, Patrick d'Hugues, D Ibarra, Anas Archane, Jérôme Jacob, Catherine Jouliau, Françoise Bodéan

### ► To cite this version:

Anne-Gwenaëlle Guezennec, Patrick d'Hugues, D Ibarra, Anas Archane, Jérôme Jacob, et al.. Influence of dissolved oxygen on the bioleaching efficiency of a mesophile to moderate thermophile consortium under oxygen enriched atmosphere. Biohydrometallurgy '16, Jun 2016, Falmouth, United Kingdom. hal-01298612

**HAL Id: hal-01298612**

**<https://hal-brgm.archives-ouvertes.fr/hal-01298612>**

Submitted on 6 Apr 2016

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# Influence of dissolved oxygen on the bioleaching efficiency of a mesophile to moderate thermophile consortium under oxygen enriched atmosphere

Anne-Gwénaëlle Guezennec<sup>1\*</sup>, D. Ibarra<sup>3</sup>, A. Archane<sup>2</sup>, J. Jacob<sup>1</sup>, F. Bodenan<sup>1</sup>, C. Joulian<sup>1</sup>, P. d'Hugues<sup>1</sup>

<sup>1</sup>Water, Environment & Ecotechnologies Division, BRGM -3, av. Claude Guillemin, BP 36009, 45060 Orléans Cedex 2, France - +33 (0)2 38 64 31 36, a.guezennec@brgm.fr

<sup>2</sup>Milton Roy Mixing, 10 rue du Bois Gasseau, 77210 Samoreau, France

<sup>3</sup>Air Liquide, CRCD, 1 chemin de la porte des Loges, BP 126, 78354 Jouy en Josas, France

## ABSTRACT

The use of oxygen is a well-known practice in high-temperature bioleaching reactors whereas air is usually preferred in medium and low-temperature operations due to economic constraints. Under high-sulphide loading conditions, as is the case with high-grade metal sulphide concentrates, the microbial and chemical demand for oxygen is significantly increased during the bioleaching process, which requires the injection of large amounts of air and thus increases the energy costs of the process. Sparging with oxygen enriched gas instead of air may offer an interesting alternative process option to improve gas transfer in the bioleaching reactor and to provide an adequate oxygen supply in order to satisfy the oxygen demand. However the use of such conditions can lead to much higher DO concentrations than those encountered with air sparging. Very few papers have been devoted to the study of the optimal range of DO concentrations for bioleaching processes. However most of them reported an inhibitory effect of DO concentrations above 5 mg.L<sup>-1</sup>. The purpose of this study was to investigate the influence of DO on the bioleaching efficiency under oxygen-enriched atmosphere in a 20L stirred tank reactor at 40°C. Bioleaching experiments were performed in continuous mode with a sulfide-rich tailings waste (pyrite 60%, copper 0.8%, cobalt 0.06 %, gold 1 g/t) using the "BRGM-KCC" bacterial consortium. The solid load was closed to 20% (w/w) and the composition of the gas injected in the reactor was: O<sub>2</sub> 55%, CO<sub>2</sub>: 1%, N<sub>2</sub>: 44%. The DO concentration in the reactor was varied between 2 and 15 mg/L by increasing the gas flow. The results obtained show a good bacterial oxidizing activity (ratio Fe<sup>III</sup>/Fe<sup>II</sup> around 1000). No inhibitory effect of the DO was observed and the sulfide dissolution yield was around 70% for a residence time of 2.3 days.

Key-words: bioleaching, oxygen, DO concentration, sulphide