

Robustness of a hybrid simulation-based/Bayesian approach for the risk assessment of a real-world road network

Pierre Gehl, Francesco Cavalieri, Paolo Franchin, Caterina Negulescu

► To cite this version:

Pierre Gehl, Francesco Cavalieri, Paolo Franchin, Caterina Negulescu. Robustness of a hybrid simulation-based/Bayesian approach for the risk assessment of a real-world road network. 12th International Conference on Structural Safety

Reliability (ICOSSAR 2017), Aug 2017, Vienne, Austria. 2017, <<http://www.icossar2017.org/>>. <hal-01529377>

HAL Id: hal-01529377

<https://hal-brgm.archives-ouvertes.fr/hal-01529377>

Submitted on 30 May 2017

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Robustness of a hybrid simulation-based/Bayesian approach for the risk assessment of a real-world road network

Pierre Gehl^a, Francesco Cavalieri^b, Paolo Franchin^b and Caterina Negulescu^a

^aRisks and Prevention Division, BRGM, France

^bDepartment of Structural & Geotechnical Engineering, Sapienza Università di Roma, Italy

Abstract

Bayesian Networks (BNs) have emerged as an appealing alternative to simulation-based methods for the risk assessment of infrastructure systems. This is mainly due to their ability (i) to explore extreme loss events if an exact inference algorithm is used and (ii) to carry out backward analyses, thus acting as a decision support system for the studied event. However, the complete probabilistic description of a spatialized infrastructure generates computational costs which increase exponentially with the number of components present in the system, despite recent efforts to design smart BN formulations that decompose the size of the problem. Moreover, such approaches have only been demonstrated for connectivity problems; unfortunately, more elaborate performance indicators based on capacity or serviceability are essential to properly capture the degraded response of a system.

Therefore this paper demonstrates the ability of a hybrid simulation-based/Bayesian approach to tackle real-world systems, also accounting for their serviceability. This hybrid method, referred to as “thrifty-naïve” formulation, may be decomposed into the following steps:

- Simulation of a given number N of deterministic scenarios for the whole system (e.g. n components), by sampling various sources of uncertainties;
- Selection of a reduced number k of components that have a significant influence on the performance of the infrastructure, by evaluating the correlations of the Monte Carlo outcomes with the system’s response;
- Construction of the corresponding BN following a naïve formulation, with only the selected k components linked to the BN nodes, P , representing the system’s performance;
- Assembly of the conditional probability tables for P nodes by counting the Monte Carlo outcomes, without requiring any specific connectivity or capacity rules.

The proposed approach presents the merit of accessing any type of performance indicator, as long as it has been generated in the simulation phase. Moreover, the inference abilities of the BN are still exploitable in order to integrate field observations and to provide a decision support to the physical layer, which is represented by the Monte Carlo simulations.

After obtaining encouraging results with virtual networks, the robustness of the thrifty-naïve BN formulation is demonstrated on a real-world application. The studied infrastructure is a road network connecting a dozen of small towns in the Pyrénées mountains (France), while being exposed to earthquakes or earthquake-triggered landslides. Informative performance measures such as the elongated travel distance or the additional travel time (if an adequate traffic model is available) may be accessed thanks to the hybrid BN method.